

The `revtex4-1` document class of the American Physical Society *

Arthur Ogawa †

Version 4.1s, dated 2020/09/30

This file embodies the implementation of the APS REVTeX 4.1 document class for electronic submissions to journals.

The distribution point for this work is <http://publish.aps.org/revtex4/>, which contains fully unpacked, prebuilt runtime files and documentation.

Contents

1	Using REVTeX	3
1.1	Bill of Materials	3
1.1.1	Primary Source	3
1.1.2	Generated by <code>latex ltxfront.dtx</code>	3
1.1.3	Generated by <code>tex ltxfront.dtx</code>	3
1.1.4	Documentation	3
1.1.5	Auxiliary	3
2	Code common to all modules	3
3	The doc module doc	4
3.1	The Preamble	4
3.1.1	Docstrip and info directives	5
3.2	The “Read Me” File	5
3.3	A Gnuly Created Sample Document	8
3.4	The Document Body	9
4	Using this package	9
4.1	Invoking the package	9
5	Frontmatter commands	10

*Work under hire to The American Physical Society.

†First revision of REVTeX4.0 (unreleased) by David Carlisle

6	The Front Matter	10
6.1	Setting the title	10
6.2	Specifying a date	10
6.3	Specifying authors and affiliations	10
6.3.1	Collaborations	12
6.3.2	Footnotes for authors, collaborations, affiliations or title	12
6.3.3	Specifying first names and surnames	14
6.4	The abstract	14
6.5	PACS codes	14
6.6	Keywords	14
6.7	Institutional report numbers	15
6.8	maketitle	15
7	Compatibility with L^AT_EX’s Required Packages	15
8	Implementation of package	15
8.1	Beginning of the package DOCSTRIP module	15
8.2	Prerequisites	16
8.3	Options	16
8.4	Process package options	17
9	Kernel of Front Matter	18
9.1	Initialization	18
9.2	The title command	18
9.3	The author, affiliation, and related commands	19
9.3.1	Commands for author or collaboration	19
9.3.2	Commands for affiliation	22
9.3.3	Commands for auxiliary information	29
9.3.4	Procedures for author, collaboration, and affiliation	30
9.4	The keywords command	34
9.5	The <code>\date</code> command and related commands	34
9.6	The pacs command	34
9.7	The <code>\preprint</code> command	35
9.8	The <code>abstract</code> environment	35
9.9	Formatting the title block	38
9.9.1	Authors and affiliations in superscriptaddress style	41
9.9.2	Authors and affiliations in groupedaddress style	47
10	Package defaults	51
10.1	Printing out the “list-of” elements	54
10.2	Syntax switch	55
10.3	End of the <code>ltxfront</code> kernel	56
10.4	Remainder of the <code>ltxfront</code> package	56
	Index	58

1 Using REVTeX

The file `README` has retrieval and installation information.

User documentation is presented separately in `auguide.tex`.

The file `template.aps` is a boilerplate file.

1.1 Bill of Materials

Following is a list of the files in this distribution arranged according to provenance.

1.1.1 Primary Source

One single file generates all.

`ltxfront.dtx`

1.1.2 Generated by latex ltxfront.dtx

Typesetting the source file under L^AT_EX generates the `readme` and the `documentation`.

`00readme`

1.1.3 Generated by tex ltxfront.dtx

Typesetting the installer generates the package files.

`ltxfront.sty`

1.1.4 Documentation

The following are the online documentation:

`ltxfront.pdf`

1.1.5 Auxiliary

The following are auxiliary files generated in the course of running L^AT_EX:

`ltxfront.aux` `ltxfront.idx` `ltxfront.ind` `ltxfront.log` `ltxfront.toc`

2 Code common to all modules

We want to require only one place in this file where the version number is stated, and we also want to ensure that the version number is embedded into every generated file.

Now we declare that these files can only be used with L^AT_EX 2_ε. An appropriate message is displayed if a different T_EX format is used.

```

1 %<*doc|package>
2 \NeedsTeXFormat{LaTeX2e}[1995/12/01]%
3 %</doc|package>

```

As desired, the following modules all take common version information:

```

4 %<kernel&!package&!doc>\typeout{%
5 %<*package|doc>
6 \ProvidesFile{%
7 %</package|doc>
8 %<*kernel|package|doc>
9 ltxfront%
10 %</kernel|package|doc>
11 %<*doc>
12 .dtx%
13 %</doc>
14 %<package>.sty%
15 %<*package|doc>
16 }%
17 %</package|doc>

```

The following line contains, for once and for all, the version and date information. By various means, this information is reproduced consistently in all generated files and in the typeset documentation.

```

18 %<*doc|package|kernel>
19 %<version>
20 [2020/09/30 4.1s frontmatter package (A0,DPC)]% \fileversion
21 %</doc|package|kernel>
22 %<kernel&!package&!doc>}%

```

3 The doc module doc

This module, consisting of the present section, typesets the programmer’s documentation, generating the `00readme` and sample document as needed.

Because the only uncommented-out lines of code at the beginning of this file constitute the `doc` module itself, we can simply typeset the `.dtx` file directly, and there is thus rarely any need to generate the “doc” `DOCSTRIP` module. Module delimiters are nonetheless required so that this code does not find its way into the other modules.

The `\end{document}` command concludes the typesetting run.

```

23 %<*doc>

```

3.1 The Preamble

The programmers documentation is formatted with the `ltxdoc` class with local customizations, and with the usual code line indexing.

```

24 \documentclass{ltxdoc}
25 \RequirePackage{ltxdocext}%
26 \let\url\undefined

```

```

27 \RequirePackage[colorlinks=true,linkcolor=blue]{hyperref}%
28 \makeatletter
29 \@ifundefined{package@font}{}%
30 {\expandafter\RequirePackage\expandafter{\csname package@font\endcsname}}
31 \makeatother
32 \CodelineIndex\EnableCrossrefs % makeindex -s gind.ist ltxfront
33 \RecordChanges % makeindex -s gglo.ist -o ltxfront.gls ltxfront.glo

```

3.1.1 Docstrip and info directives

We use so many DOCSTRIP modules that we set the `StandardModuleDepth` counter to 1.

```
34 \setcounter{StandardModuleDepth}{1}
```

The following command retrieves the date and version information from this file.

```
35 \expandafter\GetFileInfo\expandafter{\jobname.dtx}%
```

3.2 The “Read Me” File

As promised above, here is the contents of the “Read Me” file. That file serves a double purpose, since it also constitutes the beginning of the programmer’s documentation. What better thing, after all, to have appear at the beginning of the typeset documentation?

A good discussion of how to write a ReadMe file can be found in Engst, Tonya, “Writing a ReadMe File? Read This” *MacTech* October 1998, p. 58.

Note the appearance of the `\StopEventually` command, which marks the dividing line between the user documentation and the programmer documentation.

The usual user will not be asked to do a full build, not to speak of the bootstrap. Instructions for carrying these processes begin the programmer’s manual.

```

36 \begin{filecontents*}{00readme.tex}
37 \title{%
38 A \LaTeX\ Package for\\the frontmatter and title page%
39 \thanks{%
40 This file has version number \fileversion,
41 last revised \filedate.%
42 }%
43 \thanks{%
44 Version \fileversion\ \copyright\ 2009 The American Physical Society
45 }%
46 }%
47
48 \author{%
49 Arthur Ogawa%
50 \thanks{\texttt{mailto:arthur\_ogawa at sbcglobal.net}}%
51 }%
52 %\iffalse
53 % For version number and date,
54 % search on "\fileversion" in the .dtx file,

```

```

55 % or see the end of the 00readme file.
56 %\fi
57 \maketitle
58
59 This file embodies the \classname{ltxfront} package,
60 the implementation and its user documentation.
61
62 The distribution point for this work is
63 \url{http://publish.aps.org/revtex},
64 which contains fully unpacked, prebuilt runtime files and documentation.
65
66 The \classname{ltxfront} package was commissioned by the American Physical Society
67 and is distributed under the terms of the \LaTeX\ Project Public License,
68 the same license under which all the portions of \LaTeX\ itself is distributed.
69 Please see \url{http://ctan.tug.org/macros/latex/base/lppl.txt} for details.
70
71 To use this document class, you must have a working
72 \TeX\ installation equipped with \LaTeXe\
73 and possibly pdftex and Adobe Acrobat Reader or equivalent.
74
75 To install, retrieve the distribution,
76 unpack it into a directory on the target computer,
77 and move the file \file{ltxfront.sty}
78 into a location in your filesystem where it will be found by \LaTeX.
79
80 To use, read the user documentation \file{ltxfront.pdf}.
81
82 \tableofcontents
83
84 \section{Processing Instructions}
85
86 The package file \file{ltxfront.sty}
87 is generated from this file, \file{ltxfront.dtx},
88 using the {\sc docstrip} facility of \LaTeX
89 via |tex ltxfront.dtx|.
90 The typeset documentation that you are now reading is generated from
91 the same file by typesetting it with \LaTeX\ or pdftex
92 via |latex ltxfront.dtx| or |pdflatex ltxfront.dtx|.
93
94 \subsection{Build Instructions}
95
96 You may bootstrap this suite of files solely from \file{ltxfront.dtx}.
97 Prepare by installing \LaTeXe\ (and either tex or pdftex) on your computer,
98 then carry out the following steps:
99 \begin{enumerate}
100
101 \item
102 Within an otherwise empty directory,
103 typeset \file{ltxfront.dtx} with \TeX\ or pdftex,
104 thereby generating the package file \file{ltxfront.sty}.

```

```

105
106 \item
107 Next typeset \file{ltxfront.dtx} with \LaTeX\ or pdflatex;
108 you will obtain the typeset documentation you are now reading,
109 along with
110 the sample document \file{ltxfront-test.tex}
111 and the file \file{00readme}.
112
113 Note: you will have to run \LaTeX, then
114 \file{makeindex} \texttt{-s gind.ist ltxfront.idx}, then
115 \file{makeindex} \texttt{-s gglo.ist -o ltxfront.gls ltxfront.glo}, then
116 \LaTeX\ again in order to obtain a valid index and table of contents.
117 \item
118 Now typeset \file{ltxfront.dtx} with \TeX (not \LaTeX),
119 thereby generating the package file \file{ltxfront.sty}.
120 \item
121 Install the following files into indicated locations within your
122 TDS-compliant \texttt{texmf} tree (you may need root access):
123 \begin{itemize}
124 \item
125 \file{$TEXMF/}\file{tex/}\file{latex/}\file{revtex/}\classname{ltxfront.sty}
126 \item
127 \file{$TEXMF/}\file{source/}\file{latex/}\file{revtex/}\classname{ltxfront.dtx}
128 \item
129 \file{$TEXMF/}\file{doc/}\file{latex/}\file{revtex/}\classname{ltxfront.pdf}
130 \end{itemize}
131 where \file{$TEXMF/} stands for \file{texmf-local/}, or some other \texttt{texmf} tree
132 in your installation.
133 \item
134 Run \texttt{mktexlsr} on \file{$TEXMF/} (you may need root access).
135 \item
136 Build and installation are now complete;
137 now put a \cmd\usepackage\texttt{\{ltxfront\}} in your document preamble!
138 \end{enumerate}
139
140 \subsection{Change Log}
141 \changes{4.0b}{1999/06/20}{Change handling of \cs{@author} to prevent parsing problems. (Helps
142 \changes{4.0b}{1999/06/20}{Gathered all code for the abstract environment together and abstract
143 \changes{4.0b}{1999/06/20}{Separate option now controls production}
144 \changes{4.0b}{1999/06/20}{Set \cs{footnote} to \LaTeX\ standard version for this scope.}
145 \changes{4.0c}{1999/11/13}{grid changes with ltxgrid}
146 \changes{4.0d}{1998/01/31}{\cs{comma@space}}
147 \changes{4.0d}{1998/01/31}{change name from \cs{tempaffiliation}}
148 \changes{4.0d}{1998/01/31}{hookify}
149 \changes{4.0d}{1998/01/31}{If empty \cs{abstractname} omit spacing}
150 \changes{4.0d}{1998/01/31}{PACS boxed to width of abstract}
151 \changes{4.0e}{2000/09/20}{Keywords on same footing as PACS}
152 \changes{4.0e}{2000/09/20}{Warn if no production}
153 \changes{4.0f}{2001/02/13}{Actually append \cs{AU@grp} to \cs{@AAClist}.}
154 \changes{4.0g}{1998/06/10}{multiple preprint commands}

```

```

155 \changes{4.0h}{1998/06/25}{Changes to support groups of affiliations}
156 \changes{4.0h}{1998/06/25}{new hook}
157 \changes{4.0l}{1998/09/01}{add optional argument handling back}
158 \changes{4.0l}{1998/09/01}{Changes to add collaboration processing, which now means doing comma
159 \changes{4.0l}{1998/09/01}{macro added}
160 \changes{4.1a}{2008-06-30}{(AO, 443) create an entry in the PDF bookmarks for the abstract via
161 \changes{4.1a}{2008-07-01}{(AO, 496) remove default prependation to \cs{email}.}
162 \changes{4.1a}{2008-07-01}{(AO, 496) remove default prependation to \cs{homepage}.}
163 \changes{4.1a}{2008/06/16}{[removed code that had been commented out}
164 \changes{4.1b}{2008/06/29}{(AO, 455) provide a \texttt{description} environment for the abstract
165 \changes{4.1b}{2008/08/02}{(AO, 486) \cs{collaboration} to work with \texttt{groupedaddress}}
166 \changes{4.1b}{2008/08/02}{Change cname \cs{AFS@opr} to \cs{AFG@opr}}
167 \changes{4.1b}{2008/08/02}{Make the syntax of this package switch optional}%
168 \changes{4.1b}{2008/08/02}{Provide for diagnostics via \cs{frontmatterverbose@sw}}
169 \changes{4.1b}{2008/08/02}{Use \cs{@affil@def} for all access to \cs{@affil}}
170 \changes{4.1b}{2008/08/02}{Use \cs{frontmatter@init} as the vehicle for all initialization}
171 \changes{4.1b}{2008/08/04}{(AO, 443) PDF Bookmark for title page}%
172 \changes{4.1b}{2008/08/04}{Provide facility \cs{affil@cutoff}: if there is only one affiliation}
173 \changes{4.1c}{2008/08/04}{Hyperref compatibility: take \cs{maketitle} back.}
174 \changes{4.1c}{2008/08/04}{Parametrize the production after the address}%
175 \changes{4.1c}{2008/08/04}{Produce PACS, keywords only if specified}%
176 \changes{4.1d}{2008/10/17}{(AO, 410) compare \cs{@tempa} to \cs{blankaffiliation}.}%
177 \changes{4.1f}{2009/07/07}{(AO, 515) Use \cs{set@footnotefont}, which is defined in ltxutil}
178 \changes{4.1g}{2009/10/05}{(AO, 535) Robustify \cs{footnote} while \cs{class@warn} is expanding}
179 \changes{4.1g}{2009/10/05}{(AO, 539) Robustify \cs{class@warn} against TOC processing}%
180 \changes{4.1i}{2009/10/18}{(AO, 540) More runtime diagnostics via \cs{frontmatterverbose@sw}}
181 \changes{4.1i}{2009/10/23}{(AO, 540) Rationalize code that appends to \cs{AF@grp}}
182 \changes{4.1i}{2009/10/23}{(AO, 540) Optimize boolean logic }
183 \changes{4.1i}{2009/10/23}{(AO, 544) Class options runinaddress and unsortedaddress stopped wor
184 \changes{4.1m}{2009/11/20}{(AO, 563) \cs{collaboration} to work with both \texttt{groupedaddress
185 \changes{4.1m}{2009/11/20}{(AO, 563) More complete runtime diagnostics via \cs{frontmatterverbo
186 \changes{4.1m}{2009/11/20}{(AO, 563) Let \cs{@collaboration@gobble} parse all three arguments o
187 \changes{4.1n}{2009/11/30}{(AO, 567) Handle \cs{noaffiliation} case}
188 \changes{4.1n}{2009/11/30}{(AO, 567) Handle punctuation for \classoption{superscriptaddress} st
189 \changes{4.1n}{2009/12/03}{(AO) remove http:// from \cs{href} call}
190 \changes{4.1n}{2010/01/02}{(AO, 571) Interface \cs{set@footnotewidth} for determining the set w
191 \changes{4.1n}{2010/01/02}{(AO, 571) allow split after last line of footnote}%
192 \changes{4.1n}{2010/01/02}{(AO, 572) Independent footnote counter for title block. Abstract foo
193
194 \end{filecontents*}

```

3.3 A Gnuly Created Sample Document

```

195 \begin{filecontents*}{ltxfront-test.tex}
196 \documentclass{article}% use any combination of titlepage, twocolumn
197 \usepackage[]{}{ltxfront}% use inactive to turn off features
198 \begin{document}
199
200 \title{Gnu Veldt Cuisine}
201

```



```

202 \author{G. Picking}
203 \thanks{Supported by a grant from the GSF.}
204 \affiliation{Acme Kitchen Products}
205
206 \author{R. Dillo}
207 \thanks{On leave during 1985.}
208 \affiliation{Cordon Puce School}
209
210 \date{24 July 1984}%
211 \revised{5 January 1985}%
212
213 \maketitle
214
215 \section{Introduction}%
216 We reproduce most features of \LaTeX\ manual, Figure C.4, p. 183.
217 \end{document}
218 \end{filecontents*}

```

3.4 The Document Body

Here is the document body, containing only a `\DocInput` directive—referring to this very file. This very cute self-reference is a common `ltxdoc` idiom.

```

219 \begin{document}%
220 \expandafter\DocInput\expandafter{\jobname.dtx}%
221 % ^^A\PrintChanges
222 \end{document}
223 %</doc>

```

4 Using this package

Once this package is installed on your filesystem, you can employ it in adding functionality to \LaTeX by invoking it in your document or document class.

4.1 Invoking the package

In your document, you can simply call it up in your preamble:

```

%\documentclass{book}%
%\usepackage{ltxfront}%
%\begin{document}
%your document here
%\end{document}

```

However, the preferred way is to invoke this package from within your customized document class:

```

%\NeedsTeXFormat{LaTeX2e}[1995/12/01]%
%\ProvidesClass{myclass}%
%\RequirePackage{ltxfront}%

```

```

%\LoadClass{book}%
%⟨class customization commands⟩
%\endinput

```

Once loaded, the package gives you access to certain procedures, usually to be invoked by a L^AT_EX command or environment.

5 Frontmatter commands

A document using this package will use commands like `\title`, `\author`, `\thanks`, the `abstract` environment and `\maketitle`. These are part of L^AT_EX's standard document classes. But this package supplements L^AT_EX syntax with additional commands, such as `\affiliation`, `\collaboration`, `\email`, `\homepage`, and others.

Furthermore, you can have multiple `\author`, `\affiliation`, and `\collaboration` commands, each with their own set of `\email`, `\homepage`, etc. commands.

6 The Front Matter

This section describes the macros this package provides for formatting the front matter of an article. The behavior and usage of these macros can be quite different from those provided in L^AT_EX 2_ε.

6.1 Setting the title

The title of the manuscript is simply specified by using the `\title{⟨title⟩}` macro. A `\\` may be used to put a line break in a long title. The `\title` command takes an optional argument, which you will use to give an abbreviated title for use in the running header.

6.2 Specifying a date

The `\date⟨date⟩` command outputs the date on the manuscript. Using `\today` will cause L^AT_EX to insert the current date whenever the file is run:

```
\date{\today}
```

6.3 Specifying authors and affiliations

Commands specifying author and affiliation have been improved to save labor for authors and in production. Authors and affiliations are arranged into groupings called, appropriately enough, *author groups*. Each author group is a set of authors who share the same set of affiliations. Author names are specified with the `\author` macro while affiliations (or addresses) are specified with the `\affiliation` macro. Author groups are specified by sequences of `\author` macros followed by `\affiliation` macros. An `\affiliation` macro applies to

all previously specified `\author` macros which don't already have an affiliation supplied.

For example, if Bugs Bunny and Roger Rabbit are both at Looney Tune Studios, while Mickey Mouse is at Disney World, the markup would be:

```
% \author{Bugs Bunny}
% \author{Roger Rabbit}
% \affiliation{Looney Tune Studios}
% \author{Mickey Mouse}
% \affiliation{Disney World}
```

The default is to display this as

Bugs Bunny and Roger Rabbit
Looney Tune Studios
Mickey Mouse
Disney World

This layout style for displaying authors and their affiliations is chosen by selecting the class option `groupedaddress`. This option is the default for all APS journal styles, so it does not need to be specified explicitly. The other major way of displaying this information is to use superscripts on the authors and affiliations. This can be accomplished by selecting the class option `superscriptaddress`. To achieve the display

Bugs Bunny,¹ Roger Rabbit,^{1,2} and Mickey Mouse²
¹*Looney Tune Studios*
²*Disney World*

one would use the markup

```
% \author{Bugs Bunny}
% \affiliation{Looney Tune Studios}
% \author{Roger Rabbit}
% \affiliation{Looney Tune Studios}
% \affiliation{Disney World}
% \author{Mickey Mouse}
% \affiliation{Disney World}
```

Note that this package takes care of any commas and *and*'s that join the author names together and font selection, as well as any superscript numbering. Only the author names and affiliations should be given within their respective macros.

There is a third class option, `unsortedaddress`, for controlling author/affiliation display. The default `groupedaddress` will actually sort authors into the appropriate author groups if one chooses to specify an affiliation for each author. The markup:

```
% \author{Bugs Bunny}
% \affiliation{Looney Tune Studios}
% \author{Mickey Mouse}
```

```
% \affiliation{Disney World}
% \author{Roger Rabbit}
% \affiliation{Looney Tune Studios}
```

will result in the same display as for the first case given above even though Roger Rabbit is specified after Mickey Mouse. To avoid Roger Rabbit being moved into the same author group as Bugs Bunny, use the `unsortedaddress` option instead. In general, it is safest to list authors in the order they should appear and specify affiliations for multiple authors rather than one at a time. This will afford the most independence for choosing the display option. Finally, it should be mentioned that the affiliations for the `superscriptaddress` are presented and numbered in the order that they are encountered. This means that the order will usually follow the order of the authors. An alternative ordering can be forced by including a list of `\affiliation` commands before the first `\author` in the desired order. Then use the exact same text for each affiliation when specifying them for each author.

If an author doesn't have an affiliation, the `\noaffiliation` macro may be used in the place of an `\affiliation` macro.

6.3.1 Collaborations

A collaboration name can be specified with the `\collaboration` command. This is very similar to the `\author` command. It should appear at the end of an author group. The collaboration name will appear centered in parentheses. You may have multiple author groups, each with its own `\collaboration`. Because collaborations don't normally have affiliations, one needs to follow the `\collaboration` with `\noaffiliation`.

6.3.2 Footnotes for authors, collaborations, affiliations or title

Often one wants to specify additional information associated with an author, collaboration, or affiliation such as an e-mail address, an alternate affiliation, or some other ancillary information. This package introduces several new macros just for this purpose. They are:

- `\email[optional text]{e-mail address}`
- `\homepage[optional text]{URL}`
- `\altaffiliation[optional text]{affiliation}`
- `\thanks{miscellaneous text}`

In the first three, the *optional text* will be prepended before the actual information specified in the required argument. `\email` and `\homepage` each have a default text for their optional arguments ('Electronic address:' and 'URL:' respectively). The `\thanks` macro should only be used if one of the other three do not apply. Any author name can have multiple instances of these four commands. Note that unlike the `\affiliation` macro, these macros only apply to the `\author` that

directly precedes it. Any `\affiliation` *must* follow the other author-specific macros. A typical usage might be as follows:

```
% \author{Bugs Bunny}
% \email[E-mail me at: ]{bugs@looney.com}
% \homepage[Visit: ]{http://looney.com/}
% \altaffiliation[Permanent address: ]
%           {Warner Brothers}
% \affiliation{Looney Tunes}
```

This would result in the footnote “E-mail me at: bugs@looney.com, Visit: http://looney.com/, Permanent address: Warner Brothers” being attached to Bugs Bunny. Note that:

- Only an e-mail address, URL, or affiliation should go in the required argument in the curly braces.
- The font is automatically taken care of.
- An explicit space is needed at the end of the optional text if one is desired in the output.
- Use the optional arguments to provide customized text only if there is a good reason to.

The `\collaboration`, `\affiliation`, or even `\title` can also have footnotes attached via these commands. If any ancillary data (`\thanks`, `\email`, `\homepage`, or `\altaffiliation`) are given in the wrong context (e.g., before any `\title`, `\author`, `\collaboration`, or `\affiliation` command has been given), then a warning is given in the TeX log, and the command is ignored.

Duplicate sets of ancillary data are merged, giving rise to a single shared footnote. However, this only applies if the ancillary data are identical: even the order of the commands specifying the data must be identical. Thus, for example, two authors can share a single footnote indicating a group e-mail address.

Duplicate `\affiliation` commands may be given in the course of the front matter, without the danger of producing extraneous affiliations on the title page. However, ancillary data should be specified for only the first instance of any particular institution’s `\affiliation` command; a later instance with different ancillary data will result in a warning in the TeX log.

It is preferable to arrange authors into sets. Within each set all the authors share the same group of affiliations. For each author, give the `\author` (and appropriate ancillary data), then follow this author group with the needed group of `\affiliation` commands.

If affiliations have been listed before the first `\author` macro to ensure a particular ordering, be sure that any later `\affiliation` command for the given institution is an exact copy of the first, and also ensure that no ancillary data is given in these later instances.

A journal may determine the placement of these ancillary information footnotes. One journal may put all such footnotes at the start of the bibliography

while another journal may display them on the first page, as a footnote. One can override a journal style's default behavior by specifying explicitly the class option `bibnotes` (puts the footnotes at the start of the bibliography) or `nobibnotes` (puts them on the first page).

6.3.3 Specifying first names and surnames

Many authors have names in which either the surname appears first or in which the surname is made up of more than one name. To ensure that such names are accurately captured for indexing and other purposes, the `\surname` macro should be used to indicate which portion of a name is the surname. Similarly, there is a `\firstname` macro as well, although usage of `\surname` should be sufficient. If an author's surname is a single name and written last, it is not necessary to use these macros. These macros do nothing but indicate how a name should be indexed. Here are some examples;

```
% \author{Andrew \surname{Lloyd Weber}}
% \author{\surname{Mao} Tse-Tung}
```

6.4 The abstract

An abstract for a paper is specified by using the `abstract` environment:

```
% \begin{abstract}
% Text of abstract
% \end{abstract}
```

Note that with this package, the abstract must be specified before the `\maketitle` command, and there is no need to embed it in an explicit minipage environment.

6.5 PACS codes

Some authors are asked to supply suggested PACS codes with their submissions. The `\pacs` macro is provided as a way to do this:

```
\pacs{23.23.+x, 56.65.Dy}
```

The actual display of the PACS numbers below the abstract is controlled by two class options: `showpacs` and `noshowpacs`. In particular, this is now independent of the `preprint` option. `showpacs` must be explicitly included in the class options to display the PACS codes.

6.6 Keywords

A `\keywords` macro may also be used to indicate keywords for the article.

```
\keywords{nuclear form; yrast level}
```

This will be displayed below the abstract and PACS (if supplied). Like PACS codes, the actual display of the the keywords is controlled by two classoptions: `showkeys` and `noshowkeys`. An explicit `showkeys` must be included in the `\documentclass` line to display the keywords.

6.7 Institutional report numbers

Institutional report numbers can be specified using the `\preprint` macro. These will be displayed in the upper lefthand corner of the first page. Multiple `\preprint` macros may be supplied (space is limited though, so only three or less may actually fit).

6.8 maketitle

After specifying the title, authors, affiliations, abstract, PACS codes, and report numbers, the final step for formatting the front matter of the manuscript is to issue the `\maketitle` command:

```
\maketitle
```

This command must follow all of the macros listed above. The macro will format the front matter in accordance with the various class options that were specified in the `\documentclass` line (either implicitly through defaults or explicitly).

7 Compatability with L^AT_EX's Required Packages

Certain packages, usually ones written by members of the L^AT_EX Project itself, have been designated “required” and are distributed as part of standard L^AT_EX. These packages have been placed in a privileged position vis á vis the L^AT_EX kernel in that they override the definitions of certain kernel macros.

The `ltxfront` package will be incompatible with any package that redefines any of the kernel macros that `ltxfront` patches—if that package is loaded *after* `ltxfront`.

Hereinafter follows some notes on specific L^AT_EX packages.

8 Implementation of package

8.1 Beginning of the package DOCSTRIP module

```
224 %<*package>
225 \def\package@name{ltxfront}%
226 \expandafter\PackageInfo\expandafter{\package@name}{%
227 Title page macros for \protect\LaTeXe,
228 by A. Ogawa (arthur_ogawa at sbcglobal.net)%
229 }%
```

8.2 Prerequisites

This package requires the use of the `ltxutil` package.

```
230 \let\class@name\package@name
231 \RequirePackage{ltxutil}%
232 %</package>
```

End of the preliminary portion of the package code.

8.3 Options

Package options are treated in this portion of the dtx file. This portion is guarded by the `options docstrip` code so that it can be merged into a larger package gracefully.

```
233 %<*options>
```

Package option turns on diagnostics that trace its operation. `\frontmatterverbose@sw` is set false by default: we do not elect to monitor the workings of these procedures.

```
234 \DeclareOption{frontmatterverbose}{\@booleantrue\frontmatterverbose@sw}%
235 \@booleanfalse\frontmatterverbose@sw
```

Package option inactivates its syntax, for testing purposes.

```
236 \DeclareOption{inactive}{\@booleanfalse\frontmatter@syntax@sw}%
237 \@booleantrue\frontmatter@syntax@sw
```

`\runinaddress@sw` The flag `\runinaddress@sw` signifies that author addresses are to be set on the same line with the author.

The `runinaddress` option is the only one that sets `\runinaddress@sw` to true.

FIXME: this option pertains to cases where `\groupauthors@sw` is true, but is independant of `\@affils@sw`. So, it should be possible to assert both `runinaddress` and `unsortedaddress` as well as each separately.

```
238 \@booleanfalse\runinaddress@sw
```

`\@affils@sw` If `\@affils@sw` is false, an address is never recognised as “new” and is therefore always entered into the affiliation list, stopping groups of authors at the same address being consolidated into the same list: the address will be printed the same number of times it is entered.

The `unsortedaddress` option is the only one that sets `\@affils@sw` to false.

```
239 \@booleantrue\@affils@sw
```

`\groupauthors@sw` The flag `\groupauthors@sw` signifies that authors are to be grouped, affecting the meaning of `\@author@present`.

Clients will want to set `\groupauthors@sw` true if they want grouped addresses or either of the following variants: for unsorted addresses: set `\@affils@sw` false; for run-in addresses, set `\runinaddress@sw` true.

```
240 \@booleanfalse\groupauthors@sw
```


`groupedaddress` If we take the `groupedaddress` option as the default, then we can look upon the `superscriptaddress` option as simply turning `\groupauthors@sw` to `\false@sw`. `groupedaddress`, the default in APS journals, groups authors above a common address.

```
241 \DeclareOption{groupedaddress}{\clo@groupedaddress}%
242 \def\clo@groupedaddress{%
243   \@booleantrue\groupauthors@sw
244   \@booleantrue\@affils@sw
245   \@booleanfalse\runinaddress@sw
246 }%
```

`unsortedaddress` `unsortedaddress` is similar to `groupedaddress`, but turns off `\@affils@sw`, with the result that each address that is entered will be printed.

```
247 \DeclareOption{unsortedaddress}{\clo@unsortedaddress}%
248 \def\clo@unsortedaddress{%
249   \@booleantrue\groupauthors@sw
250   \@booleanfalse\@affils@sw
251   \@booleanfalse\runinaddress@sw
252 }%
```

`runinaddress` `runinaddress` is similar to `groupedaddress`, with the addition of the Boolean `\runinaddress@sw`, which causes the authors associated with a particular address group to be formatted in a paragraph instead of on separate lines.

```
253 \DeclareOption{runinaddress}{\clo@runinaddress}%
254 \def\clo@runinaddress{%
255   \@booleantrue\groupauthors@sw
256   \@booleantrue\@affils@sw
257   \@booleantrue\runinaddress@sw
258 }%
```

`superscriptaddress` `superscriptaddress` presents author affiliations as superscripts. Authors with like affiliations share the same superscript.

FIXME: if `\groupauthors@sw` is false, would not `\@affils@sw` be a don't care?

```
259 \DeclareOption{superscriptaddress}{\clo@superscriptaddress}%
260 \def\clo@superscriptaddress{%
261   \@booleanfalse\groupauthors@sw
262   \@booleantrue\@affils@sw
263   \@booleanfalse\runinaddress@sw
264 }%
```

```
265 %</options>
```

8.4 Process package options

```
266 %<*package>
267 \DeclareOption*{\OptionNotUsed}%
268 \ProcessOptions*
269 %</package>
```

9 Kernel of Front Matter

Here begins the kernel of the `frontmatter` package.

```
270 %<*kernel>
```

This package implements a new syntax for the title page of an article.

Special acknowledgment: this package uses concepts pioneered and first realized by William Baxter (mailto:web at superscript.com) in his SuperScript line of commercial typesetting tools, and which are used here with his permission.

These macros were first coded by David P. Carlisle for the American Physical society in the late 1990s as part of the development of REVTeX4. That development work was taken over by Arthur Ogawa, who is the author of this package.

9.1 Initialization

`\frontmatter@init` The `\frontmatter@init` procedure sets up all the registers for processing the title page. At present, this is done once, at `\class@documenthook` time. If multiple title pages are to be processed within a job, the initialization must be done for each.

```
271 \appdef\class@documenthook{\frontmatter@init}%
```

```
272 \let\frontmatter@init\@empty
```

9.2 The title command

`\title` The author uses `\title` to specify the title. As in the AMS classes, `\title` has an optional argument specifying a short form for use in running heads.

`\do@title`

Once the `\title` is given, you can specify any combination of `\thanks`, `\email`, `\homepage`, and `\altaffiliation` commands, applying to the title of the document.

Compatibility note: as with all of the standard L^AT_EX commands that we override, we make here a private definition and later switch it in if so required.

```
273 \newcommand\frontmatter@title[2] []{%
```

```
274 \def\@title{#2}%
```

```
275 \def\@shorttitle{#1}%
```

```
276 \let\@AF@join\@title@join
```

```
277 }%
```

`\@title` The arguments to `\title` are saved in these internal macros, which are set up to produce a warning if `\title` has not been used before `\maketitle`.

`\@shorttitle`

Extensibility note: by using `\frontmatter@init` as the initialization procedure, we open the possibility of more than one title page per document.

```
278 \appdef\frontmatter@init{%
```

```
279 \def\@title{\class@warn{No title}}%
```

```
280 \let\@shorttitle\@empty
```

```
281 \let\@title@aux\@title@aux@cleared
```

```
282 }%
```

```

\@title@join
\@title@join@ 283 \def\@title@join{\expandafter\@title@join@\@title@aux}%
\@title@aux@cleared 284 \def\@title@join@#1#2{%
285 \def\@title@aux{\@join{\@separator}{#1}{#2}}}%
286 }%
287 \def\@title@aux@cleared{}}%

```

9.3 The author, affiliation, and related commands

`\c@affil` `\c@affil` stores the affiliation numbers used for the superscript marks. The `\c@collab` `\newcounter` command defines `\theaffil`, which we never use: this counter is evaluated solely via `\the`.

`\c@collab` stores the collaboration numbers. The `\newcounter` command defines `\thecollab`. As with `\c@affil`, we never use `\thecollab`; only `\the` `\c@collab`.

Each counter must be cleared before frontmatter can be processed.

```

288 \newcounter{affil}%
289 \newcounter{collab}%
290 \appdef\frontmatter@init{%
291 \c@affil\z@
292 \c@collab\z@
293 }%

```

9.3.1 Commands for author or collaboration

`\author` Each author is given in a *separate* `\author` command. This is similar to the AMS classes, but the AMS also try to support the `article` class's `\and` command for putting multiple authors in one `\author` command. This package, however, does not support the `\and` command.

When the `\author` command is encountered, the previous author, author group, affiliation, and affiliation group are at an end. This procedure moves the previous author to the author group (`\move@AU`), moves the previous affiliation to the affiliation group (`\move@AF`), and terminates the previous author/affiliation group (`\move@AUAF`) as the case may require.

Compatibility note: as with all of the standard L^AT_EX commands that we override, we make here a private definition and later switch it in if so required.

```

294 \newcommand\frontmatter@author{% implicit #1
295 \@author@def{}}% implicit #2
296 }%

```

`\collaboration` Specify the collaboration (given after a group of authors).

This procedure does exactly what `\author` does, and sets a flag signifying that the `\collaboration` command was given.

Note: earlier versions attempted to ignore the collaboration command if it was considered inappropriate. We must not do this, however, because it throws the state machine out of kilter.

```

297 \def\collaboration{% implicit #1

```

```

298 \@author@def{\@booleantrue\collaboration@sw}% implicit #2
299 }%
300 \appdef\frontmatter@init{%
301 \@booleanfalse\collaboration@sw
302 }%

```

`\@author@init` Here are all the access procedures for the author data structure.

`\@author@cleared` We define a flag value for `\@author(private)`, a procedure `\@author@gobble`

`\@authorclear@sw` to read author data without any effect, a procedure for setting `\@author`

`\@author@def` to the flag value (`\@author@init`), a Boolean to test against the flag value

`\@author@join@` (`\@authorclear@sw`), and a procedure to add new ancillary data to the author.

`\@author@join` Note that expanding the functionality of the `\collaboration` command entailed changing the data structures, because now all authors must remember the collaboration they belong to. This change affects procedures `\@author@cleared` and `\@author@gobble`.

```

303 \def\@author@cleared{}{}%
304 \def\@author@gobble#1#2#3{}%
305 \def\@author@init{%
306 \let\@author\@author@cleared
307 \@booleanfalse\collaboration@sw
308 }%
309 \def\@authorclear@sw{\ifx\@author\@author@cleared}%
310 \appdef\frontmatter@init{%
311 \@author@init
312 }%

313 \def\@author@def#1#2{%
314 \frontmatterverbose@sw{\typeout{\string\author\space\string\collaboration}}{}%
315 \move@AU\move@AF\move@AUAF
316 \let\@AF@join\@author@join
317 #1%
318 \def\@author{{#2}}%
319 }%
320 \def\@author@join#1#2#3{%
321 \def\@author{{#1}{\@join{\@separator}{#2}{#3}}}%
322 }%
323 \def\@author@join{\expandafter\@author@join@\@author}%

```

`\move@AU` The `\move@AU` procedure moves the most recent author to the current author group

`\add@AU@CO@grp` `\AU@grp`, or the most recent collaboration to the collaboration group `\CO@grp`. If we recently did a `\@author@init`, this is a no-op.

To accommodate the expanded syntax of `\collaboration`, we add a new field to those associated with an author (collaborator), namely the value of the collaboration counter.

```

324 \def\move@AU{%
325 \@authorclear@sw{}%
326 \collaboration@sw{}%
327 \advance\c@collab\@ne
328 \@argswap{\CO@grp\CO@opr}%

```

```

329 }-%
330 \@argswap{\AU@grp\AU@opr}%
331 }%
332 {%
333 \expandafter\@argswap@val
334 \expandafter{\@author}%
335 {\expandafter\@argswap@val\expandafter{\the\c@collab}{\add@AU@CO@grp}}%
336 }%
337 }%
338 \@author@init
339 }%

```

The procedure `\add@AU@CO@grp` adds to the specified group #3 using the given intercolated operator #4, with arguments {#1} and #2, where the first argument is the collaboration number, the second is the author name, and the third the joined attributes of the author. For example, `\move@AU` could finally execute: `\appdef \AU@grp {\AU@opr{1}{A. Author}}{}`.

```

340 \def\add@AU@CO@grp#1#2#3#4{%
341 \appdef#3{#4{#1}#2}%
342 \frontmatterverbose@sw{\say#3}{}%
343 }%

```

`\@author@finish` We define a procedure to terminate author/affiliation parsing just before the title block is formatted. We detect the case where an author group is not followed by an affiliation group.

We first finish off any author- or affiliation groups in progress. Next, we detect the case where there is an author group or a collaboration group in progress, but no affiliation group. If so, we emit a diagnostic message and act as if a `\noaffiliation` command had been given. In any case, we finish off any author/affiliation pair that may remain. Formatting of the title block may now proceed.

```

344 \def\@author@finish{%
345 \frontmatterverbose@sw{\typeout{\string\@author@finish}}}%
346 \move@AU\move@AF
347 \@ifx{\AU@grp\@empty}{%
348 \@ifx{\CO@grp\@empty}%
349 }{%
350 \false@sw
351 }%
352 }-%
353 \@ifx{\AF@grp\@empty}{%
354 \beginingroup
355 \let\href\@secondoftwo
356 \let\AU@opr\@secondofthree
357 \let\CO@opr\@secondofthree
358 \let\footnote\@gobble
359 \@ifx{\CO@grp\@empty}{%
360 \class@warn{Assuming \string\noaffiliation\space for authors}%
361 \frontmatterverbose@sw{\say\AU@grp}%

```

```

362   }{%
363   \class@warn{Assuming \string\noaffiliation\space for collaboration}%
364   \frontmatterverbose@sw{\say\C0@grp}{}%
365   }%
366   \endgroup
367   \@affil@none\move@AF
368   }{%
369   }%
370   \move@AUAF
371   }%
372   \def\@secondofthree#1#2#3{#2}%

```

`\@join` The procedure `\@join` inserts a separator between two tokens, or, if the first token is nil, elides both that token and the separator.

```

373 \def\@join#1#2#3{%
374   \@ifempty{#2}{#3}{#2#1#3}%
375 }%
376 \def\@separator{;\space}%

```

`\surname` No-op to allow better post-processing of the file.
`\firstname` 377 `\let\surname\@firstofone`
 378 `\let\firstname\@firstofone`

`\and` The original L^AT_EX idea of using one `\author` command to capture all authors and their address just doesn't work with multiple authors possibly sharing addresses, so in this class disable `\and`.

```

379 \newcommand\frontmatter@and{\class@err{\protect\and\space is not supported}}

```

9.3.2 Commands for affiliation

`\affiliation` After each group of authors with the same address, give that address in `\affiliation`. If later in the list you have an author with the address of an earlier author, repeat the `\affiliation` command: the system will detect the equivalence and (if using the `superscriptaddress` option) only print the affiliation once, reusing the superscript marker.

When the `\affiliation` command is encountered, the current author and author group (if any) are at an end. Also, the current affiliation is at an end.

FIXME: changes to catcode required elsewhere now?

```

380 \def\cat@comma@active{\catcode'\,\active}%
381 {\cat@comma@active\gdef,{\active@comma}}%
382 \def\active@comma{,\penalty-300\relax}%
383 \newcommand\affiliation{%
384   \frontmatterverbose@sw{\typeout{\string\affiliation}}{%
385     \move@AU\move@AF
386     \begingroup
387     \cat@comma@active
388     \@affiliation
389   }%

```

```

390 \def\@affiliation#1{%
391 \endgroup
392 \let\@AF@join\@affil@join
393 \@affil@def{#1}%
394 }%

```

`\noaffiliation` User-level command `\noaffiliation` signifies that the current group of authors, or the current collaboration, has *no* affiliation.

This is implemented by acting as if the `\affiliation` command has been given, and using a flag value of `{\relax}`, which adds an element to the affiliation group of this author, albeit a nil one (`\AFF@opr {\relax} {}`).

Note that this procedure does substantially the same as `\@author@finish`. (the latter, If it does not bail out altogether, differs chiefly in providing diagnostics).

```

395 \newcommand\frontmatter@noaffiliation{%
396 \frontmatterverbose@sw{\typeout{\string\noaffiliation}}{}%
397 \move@AU\move@AF

```

In `\@author@finish`, there is code testing if an effective `\noaffiliation` should be executed now. Here, we do so in any case.

```

398 \@affil@none\move@AF
399 \move@AUAF
400 }%
401 \def\blankaffiliation{}%

```

`\@affil@cleared` Here are all the access procedures for the affiliation data structure. Note the similarity to those of the `\@author` data structure.

`\@affil@init` We define a flag value for `\@affil` (private), a procedure for setting `\@affil` to the flag value (`\@affil@init`), a Boolean to test against the flag value

`\@affil@clear@sw` (`\@affil@clear@sw`), a procedure `\@affil@def` to load a value into the structure, and a procedure to add new ancillary data to the affiliation.

```

\@affil@join@ 402 \def\@affil@cleared{{{}{}}}%
\@affil@join 403 \def\@affil@nil{{\relax}}}%
404 \appdef\frontmatter@init{%
405 \@affil@init
406 }%
407 \def\@affil@none{%
408 \let\@affil\@affil@nil
409 }%
410 \def\@affil@init{%
411 \let\@affil\@affil@cleared
412 }%
413 \def\@affil@clear@sw{\@ifx{\@affil\@affil@cleared}}}%
414 \def\@affil@def#1{%
415 \def\@affil{#1}}}%
416 }%
417 \def\@affil@join@#1#2#3{%
418 \def\@affil{#1}{\@join{\@separator}{#2}{#3}}}%
419 }%

```

```
420 \def\@affil@join{\expandafter\@affil@join@\@affil}%
```

`\move@AF` Move the most recent affiliation to the affiliation group. If we recently did a `\@affil@init`, this is a no-op.

Set the `\temp@sw` to false, then execute the affiliation list (`\@AFF@list`) with the intercolated operator set to `\@affil@match` and with `\@tempa` holding the first component of `\@affil`, the current affiliation, which is to be matched.

If the current affiliation has been seen before, then by side effect `\temp@sw` will be set to true, `\@tempc` will be set to the matching affiliation number, and `\@tempd` will be set to the affiliation’s ancillary data. The Boolean `\@affils@sw` being false prevents this test from ever returning a “true” result.

This procedure uses `\@tempa` and sets `\@tempc`, `\@tempd`, and `\temp@sw`.

```
421 \def\move@AF{%
422   \@affilclear@sw}{%
423   \@booleanfalse\temp@sw
424   \let\@tempd\@empty
425   \@affils@sw{%
426     \expandafter\@affil@addr@def\expandafter\@tempa\@affil
427     \def\AFF@opr{\@affil@match\@tempa}%
428     \@AFF@list
429   }{\temp@sw
```

True clause: This affiliation has been seen before. If ancillary data for the affiliation have been given, but are not identical to those seen before, give a warning.

```
430   {%
431     \expandafter\@affil@aux@def\expandafter\@tempb\@affil
432     \@ifx{\@tempb\@empty}{\}%
433     \@ifx{\@tempb\@tempd}{\}%
434     \class@warn{%
435       Ancillary information for \@tempa\space must not be different!
436       Please put all of it on the first instance%
437     }%
438   }%
439 }%
440 }%
```

False clause: This affiliation is a new one: increment the affiliation counter to get a unique affiliation ID and append the new ID, collaboration number, address, and auxiliary information to the list `\@AFF@list`.

Note that, with the expanded syntax of `\collaboration`, we need to label each address with its associated collaboration.

Note also that the `\noaffiliation` case is handled by recognizing the flag value `\@affil@nil`.

```
441   {%
442     \@ifx{\@affil\@affil@nil}{%
443       \def\@tempc{0}%
444       \@argswap@val{0}%
445     }{\%
446       \advance\c@affil\@ne
```



```

447 \expandafter\def\expandafter\@tempc\expandafter{\the\c@affil}%
448 \expandafter\@argswap@val\expandafter{\the\c@affil}%
449 }%
450 {%
451 \expandafter\@argswap@val\expandafter{\the\c@collab}{%
452 \expandafter\@argswap@val\expandafter{\@affil}{%
453 \add@list@val@val@val\@AFF@list\AFF@opr
454 }%
455 }%
456 }%
457 }%

```

In either case, append this affiliation number to the `\AF@grp`, the affiliation group of the current author group. (It will later be considered for the `\@AFG@list`.) Then assign the flag value to `\@affil` that signifies it has been cleared.

```

458 \appdef@eval\AF@grp\@tempc
459 \frontmatterverbose@sw{\say\AF@grp}{}%
460 \@affil@init
461 }%
462 }%
463 \def\@affil@addr@def#1#2#3{%
464 \def#1{#2}%
465 }%
466 \def\@affil@aux@def#1#2#3{%
467 \def#1{#3}%
468 }%

```

Procedure `\add@list@val@val@val` appends to the given list `#1` using the given intercollated operator `#2`, with arguments `#5` (affiliation ID) and `#4` (collaboration ID) delimited by braces, and `#3` bare. In the end, `\move@AF` may execute something like `\appdef \@AFF@list \AFF@opr {1} {3} {My Institution} {thanks}`.

```

469 \def\add@list@val@val@val#1#2#3#4#5{%
470 \appdef#1{#2{#5}{#4}#3}%
471 \frontmatterverbose@sw{\say#1}{}%
472 }%

```

`\@affil@match` The procedure `\@affil@match` is the definition for `\AFF@opr`, the intercollated operator for `\@AFF@list`, when adding a new affiliation: it seeks a match with any earlier affiliation. When the affiliation list is executed, this procedure tests each entry against the ‘new’ affiliation (which has been stored in `\@tempa`) and its associated collaboration number (in `\@tempb`).

If `\groupauthors@sw` is true, then we require the collaboration ID to match, otherwise there is no such requirement, as is appropriate for the `superscriptaddress` class option.

Uses `\temp@sw`, `\@tempc`, and `\@tempd` to communicate back: if it returns `\temp@sw` true, a match was found. Then `\@tempc` will be the affiliation ID of the matching entry and `\@tempd` will be the auxiliary information of the matching entry.

```

473 \def\@affil@match#1#2#3#4#5{%

```

```

474 \temp@sw}{%
475 \def\@tempifx{#4}%
476 \@ifx{\@tempifx#1}{%
477 \groupauthors@sw{%
478 \ifnum{#3=\c@collab}{%
479 \true@sw
480 }{%
481 \false@sw
482 }%
483 }{%
484 \true@sw
485 }%
486 }{%
487 \false@sw
488 }%
489 {%
490 \@booleantrue\temp@sw
491 \def\@tempc{#2}%
492 \def\@tempd{#5}%
493 }{%
494 }%
495 }%
496 }%

```

`\move@AUAF` Append `\AF@grp`, `\AU@grp`, and `\CO@grp` to `\@AAC@list`, append `\CO@grp` to `\@AFG@list`, and merge any new `\AF@grp` to `\@AFG@list`.

The entire procedure is predicated on something non-trivial to move.

If both author group `\AU@grp` and affiliation group `\AF@grp` are nil, bail out.

No, try that again:

If we have seen any affiliations (`\AF@grp` is not nil), then it is time to move the current affiliation group and author group to `\@AAC@list`. If not, we are picking up authors into an author group, and we should bail out.

To extend this scheme to the new `\collaboration` abilities, we must append an affiliation `\AF@opr` to `\@AAC@list` also in the case where there was no affiliation specified (e.g., `\noaffiliation`). This affiliation will be a nil affiliation: `\AF@opr{0}`.

FIXME: only one of `\CO@grp` or `\AU@grp` is non-empty at this point, but this code does not appear to recognize this fact!

```

497 \def\move@AUAF{%
498 \frontmatterverbose@sw{\say\AU@grp\say\AF@grp\say\CO@grp}{}%
499 \@ifx{\AF@grp\@empty}{%
500 \ifx{\@empty\CO@grp}{%

```

Both `\AF@grp` and `\CO@grp` are empty: nothing to do. But what if `\AU@grp` is not empty?

```

501 }{%

```

Append the nil `\AF@opr` to `\@AAC@list`.

```

502 \appdef \@AAC@list{\AF@opr{0}}%

```

Append the collaboration group to the `\@AAC@list`; no intercollated operator need be added, because we already have `\CO@opr`.

```
503     \appdef@e   \@AAC@list{\CO@grp}%
504     \appdef@e   \@AFG@list{\CO@grp}%
505     \let\CO@grp\@empty
506     }%
507 }{%
```

Append current affiliation group (expansion of `\AF@grp`) to the author/affiliation list (`\@AAC@list`), using `\AF@opr` as the intercollated operator; also append the current authors (`\AU@grp`).

```
508     \appdef     \@AAC@list{\AF@opr}%
509     \appdef@eval\@AAC@list{\AF@grp}%
510     \appdef@e   \@AAC@list{\AU@grp}%
```

Determine if either `\AU@grp` or `\CO@grp` is non-empty.

```
511     \@ifx{\@empty\AU@grp}{%
512     \@ifx{\@empty\CO@grp}%
513     }{%
514     \false@sw
515     }%
```

At this point, there is a Boolean in T_EX's scanner; it will parse the following two brace-delimited sequences and select one of them.

```
516     {%
```

This branch is executed if and only if both `\AU@grp` and `\CO@grp` are empty.

```
517     }{%
```

There was either a `\author` or a `\collaboration` command. Append the current affiliation group to `\@AFG@list`, (only if it is not already there) using `\AFG@opr` as the intercollated operator.

Note that `\@AFG@list` is a list of *unique* affiliation *groups*, and building it entails an N^2 computation.

```
518     \@booleanfalse\temp@sw
519     \def\AFG@opr{x@match\AF@grp}%
520     \let\CO@opr\@author@gobble
521     \@AFG@list
522     \temp@sw}{%
523     \appdef     \@AFG@list{\AFG@opr}%
524     \appdef@eval\@AFG@list{\AF@grp}%
525     }%
```

If the collaboration `\CO@grp` is not empty, we append it to the `\@AFG@list` and to the `\@AAC@list`.

```
526     \@ifx{\@empty\CO@grp}{%
527     \appdef@e   \@AAC@list{\CO@grp}%
528     \appdef@e   \@AFG@list{\CO@grp}%
529     \let\CO@grp\@empty
530     }%
531     }%
```

Finally, null out the macros holding the author group `\AU@grp`, affiliation group `\AF@grp`, and collaboration group `\CO@grp`.

```

532   \let\CO@grp\@empty
533   \let\AU@grp\@empty
534   \let\AF@grp\@empty
535 }%
536 \frontmatterverbose@sw{\say\@AAC@list\say\@AFG@list}{}%
537 }%

```

`\AU@grp` The control sequence name `\AU@grp` accumulates consecutive `\author` entries (with `\AU@opr` as the intercolated operator) and `\collaboration` entries (with `\CO@opr` as the intercolated operator). Ultimately, its contents are appended to the author/affiliation list `\@AAC@list` and to the list of affiliation groups, `\@AFG@list`. It must be initialized to `\@empty`.

Note on `\AU@opr` and `\CO@opr`: it is essential to treat these two operators to the greatest extent possible on an equal footing. Therefore we invariably assign values to the pair of them within the same procedure.

The macro `\AF@grp` accumulates affiliation IDs into an affiliation group. It must be empty at the beginning of the frontmatter.

The `\@AAC@list` macro accumulates authors (using `\AU@opr` as the intercolated operator), collaborations (using `\CO@opr` as the intercolated operator), and affiliations (using `\AF@opr` as the intercolated operator).

It must be empty at the beginning of the frontmatter.

The macro `\@AFG@list` accumulates affiliation groups, with `\AFG@opr` as the intercolated operator, and collaborations, with no intercolated operator. This token list is employed when and only when `groupedaddress` is in effect.

The macro `\@AFF@list` accumulates the list of affiliations with `\AFF@opr` as the intercolated operator. It must be empty at the beginning of the frontmatter.

Each `\affiliation` command in the document contributes to this list, as long as the argument of that instance of the command is “new”.

Each entry in this list consists of the `\AFF@opr` intercolated operator followed by three brace-delimited tokens, representing, in order:

1. the affiliation’s unique ID, a number increasing monotonically for each new entry,
2. the optional argument of the `\affiliation` command, the footnote to the affiliation, and
3. the text of the affiliation.

At various junctures in the code, the control sequence name `\AFF@opr` assumes the meaning of `\@affil@group`, `\affil@script`, or is defined to expand to `\@affil@match\@tempa`, and the list `\@AFF@list` is expanded.

For each of these lists, here is the syntax of an element and the usage of the associated operator:

```

%\@AFF@list \AFF@opr{\affiliation ID}{\collaboration ID}{\address}{\auxiliary info} \frontmatter
%\@AFG@list \AFG@opr{\affiliation ID}..\{affiliation ID}\} \frontmatter@author@produce@group
%\@AAC@list \AF@opr{\affiliation ID}..\{affiliation ID}\} (\AU@opr|\CO@opr){\collaboration ID}\}
%
%\AFF@opr \@affil@match\@tempa \@affil@script \@affil@group
%\AFG@opr \affils@present@group \x@match\AF@grp
%\AF@opr \@gobble \@affilID@def \@affilID@count \AF@temp\@tempcnta \@affilID@match\AF@temp
%\AU@opr \@secondofthree \@author@count\@tempcnta \@author@present \@author@gobble \@author@count\
%\CO@opr \@secondofthree \@collaboration@count \AU@temp\@tempcnta \@collaboration@present \AU@temp \
%
%\CO@opr\@author@cleared
%

538 \appdef\frontmatter@init{%
539 \let\AU@grp\@empty
540 \let\CO@grp\@empty
541 \let\AF@grp\@empty
542 \let\@AAC@list\@empty
543 \let\@AFG@list\@empty
544 \let\@AFF@list\@empty
545 }%

```

`\@AF@join` The `\csname \@AF@join` is a procedure used within `\email`, `\homepage`, `\thanks`, and `\altaffiliation`. When such a command appears after an `\author`, `\collaboration`, or `\affiliationcommand`, the `\@AF@join` procedure appends the argument given to the appropriate macro. Its default is to give an error message, since these commands are legal only within the particular context mentioned.

```

546 \appdef\frontmatter@init{%
547 \let\@AF@join\@AF@join@error
548 }%
549 \def\@AF@join@error#1{%
550 \class@warn{%
551 \string\email, \string\homepage, \string\thanks, or \string\altaffiliation\space
552 appears in wrong context.
553 }%
554 }%

```

9.3.3 Commands for auxiliary information

`\email` Just tacks the email address on to the current author or affiliation.

```

555 \def\sanitize@url{%
556 \@makeoother\%
557 \@makeoother\~%
558 \@makeoother\_%
559 }%
560 \newcommand*\email[1] []{\begingroup\sanitize@url\@email{#1}}%
561 \def\@email#1#2{%
562 \endgroup
563 \@AF@join{#1}\href{mailto:#2}{#2}}%
564 }%

```

`\homepage` Just tacks the URL on to the current author or affiliation. Note: group opened in `\homepage` is closed in `\@homepage`.

```
565 \newcommand*\homepage[1] []{\begingroup\sanitize@url\@homepage{#1}}%
566 \def\@homepage#1#2{%
567   \endgroup
568   \@AF@join{#1\href{#2}{#2}}%
569 }%
```

`\href` The document may load a package that defines either of these commands; if not, we give a default meaning.

```
570 \appdef\class@documenthook{%
571   \providecommand\href[1] {}%
572 }%
```

`\thanks` The operative version of `\thanks` appends an item to `\@author`, or `\@affil`'s auxiliary data.

```
573 \def\frontmatter@thanks{% implicit #1
574   \@AF@join
575 }%
```

`\altaffiliation` Implemented more or less like `\thanks` but shares the affiliation counter. Optional argument may be used to give explanatory text eg 'currently staying at' This will be placed before the address, if used in a footnote.

```
576 \newcommand*\altaffiliation[2] []{%
577   \@AF@join{#1#2}%
578 }%
```

9.3.4 Procedures for author, collaboration, and affiliation

Macros that list off, say, authors, and which require punctuation, like "A, B, and C", will use `\set@listcomma@list`, `\set@listcomma@count`, `\@listand`, and `\@listcomma`. These macros use the `\@tempcnta` register to keep track of how many items remain to be listed off.

At present, `\@author@present` will decrement that counter.

`\set@listcomma@list` Pop the author count for this collaboration.

`\set@listcomma@count` Note: by side effect, it assigns `\@listcomma`: for a list of length two, suppress comma addition.

```
579 \def\set@listcomma@list#1{%
580   \expandafter\@reset@ac\expandafter#1#1{0}\@reset@ac{%
581     \let\@listcomma\relax
582   }{%
583     \let\@listcomma\@listcomma@comma
584   }%
585 }%
586 \def\set@listcomma@count#1{%
587   \@ifnum{#1}=\tw@}{%
588     \let\@listcomma\relax
```

```

589 }{%
590 \let\@listcomma\@listcomma@comma
591 }%
592 }%

```

Does the actual pop operation, then generates a Boolean which selects one of the two assignments for `\@listcomma`.

Note: this procedure sets `\@tempcnta` to reflect the number of items to list off.

```

593 \def\@reset@ac#1#2#3\@reset@ac{%
594 \def#1{#3}%
595 \@tempcnta#2\relax
596 \@ifnum{#2=\tw@}{\andname\space}{}}%
597 }%

```

`\listand` Might need extending with penalties etc.

Note: this procedure expects `\@tempcnta` to reflect the current number of items remaining to list off.

```

598 \def\@listand{\@ifnum{\@tempcnta=\tw@}{\andname\space}{}}%

```

`\@listcomma` This definition, with `\@one` puts a comma before and.

David Carlisle says: In UK English (at least) would have `\tw@` here, which would then implement the convention of indicating conjunction with comma or “and”, but not both.

Note: this procedure expects `\@tempcnta` to reflect the current number of items remaining to list off.

```

599 \def\@listcomma@comma{\@ifnum{\@tempcnta>\@one}{,}{}}%
600 \def\@listcomma@commaUK{\@ifnum{\@tempcnta>\tw@}{,}{}}%

```

`\@collaboration@gobble` This command will be the synonym of `\CO@grp` during the expansion of `\@AAC@list`, within `\affils@present@groupexecution` (in a `groupedaddress` situation).

```

601 \def\@collaboration@gobble#1#2#3{}%

```

`\doauthor` Main control over how authors are typeset.

#1 is loaded by `\author`

#2 is loaded by `\email`, `\homepage`, `\altaffiliation`, or `\thanks`

#3 is the superscript affiliation, if at all used.

First, the author name is formatted, followed by a comma, then come any marks relating to affiliation (if present), then come the homepage URL and email address, if any, with appropriate punctuation.

Here, as in `\@affil@script`, the parameter `\affil@cutoff` controls whether the argument #3 is produced as a superscript label connecting this author with its affiliation. (If there is only one affiliation on the title page, it makes sense to remove the superscript.)

Note that argument #3 must effectively execute either `\aftergroup\true@sw` or `\aftergroup>false@sw` (exactly once!). In the case of `superscriptaddress`, this is done when `\@author@present@script` invokes `\doauthor` with its third argument containing `\@affil@present@script`. Otherwise (e.g., `groupedaddress`),

`\doauthor` is invoked by `\@author@present@group` with its third argument containing `\@affil@present@group`.

```
602 \def\doauthor#1#2#3{%
603   \ignorespaces#1\unskip\@listcomma
604   \begingroup
605   #3%
```

At this point, we must have queued up a Boolean (either `\true@sw` or `\false@sw`).

```
606   \if@empty{#2}{\endgroup{}}{\endgroup{\comma@space}{}\frontmatter@footnote{#2}}%
607   \space \@listand
608 }%
```

`\x@match` Procedure `\x@match` is used as an alias `\AFG@opr`, probing the list of affiliation groups and setting a Boolean if a match is found to #1 (usually the current affiliation group).

Procedure `\y@match` is used as an alias to `\@TBN@opr`, probing the list of unique title block footnotes for a match to the footnote text: when the first match is found it sets a Boolean, defining `\@tempb` to the number of that footnote.

```
609 \def\x@match#1#2{%
610   \temp@sw{}%
611   \def\@tempifx{#2}%
612   \@ifx{\@tempifx#1}{%
613     \@booleantrue\temp@sw
614   }{%
615   }%
616 }%
617 }%
618 \def\y@match#1#2#3{%
619   \temp@sw{}%
620   \def\@tempifx{#3}%
621   \@ifx{\@tempifx#1}{%
622     \@booleantrue\temp@sw
623     \def\@tempb{#2}%
624   }{%
625   }%
626 }%
627 }%
```

`\frontmatter@footnote` Used when typesetting a title block footnote. (Item 290: merge duplicates.)

Maintains a list of frontmatter footnotes along with associated device. Uniquifies each footnote by traversing the list and looking for a match to the footnote text. If found, define `\@tempb` to the corresponding footnote device, and typeset it with `\@footnotemark`. If never found, manually increment footnote counter, determine the corresponding footnote device, and add footnote text and device to the list of frontmatter footnotes.

The list `\@FMN@list` is processed later in the title block production.

Note that this method of making footnotes runs afoul of `hyperref`'s patches of the \LaTeX kernel. Therefore, we avoid trouble by refraining from using `\@footnotemark` and by creating our own hypertext links.


```

628 \def\frontmatter@footnote#1{%
629 \begingroup
630 \@booleanfalse\temp@sw
631 \def\@tempa{#1}%
632 \let\@tempb\@empty
633 \def\@TBN@opr{\y@match\@tempa}%
634 \@FMN@list

```

By side effect, \@tempb holds the value of the footnote counter if This note has been seen before. Otherwise \temp@sw is false.

```

635 \temp@sw{%
636 \expandafter\frontmatter@footnotemark
637 \expandafter{\@tempb}%
638 }%

```

Execute \frontmatter@foot@mark, feeding it the value of the current footnote counter. This call requires two levels of pre-expansion to accomplish, the first to expand \csname, the second to evaluate \the.

```

639 \stepcounter\@mpfn
640 \expandafter\expandafter
641 \expandafter\frontmatter@foot@mark
642 \expandafter\expandafter
643 \expandafter{%
644 \expandafter \the\csname c@\@mpfn\endcsname
645 }{#1}%
646 }%
647 \endgroup
648 }%

```

Procedure \frontmatter@foot@mark lays down the footnote device (mark) and takes care of the footnote text. The latter merely involves queuing that text (along with its associated device) into \@FMN@list.

```

649 \def\frontmatter@foot@mark#1#2{%
650 \frontmatter@footnotemark{#1}%
651 \g@addto@macro\@FMN@list{\@TBN@opr{#1}{#2}}%
652 }%
653 \appdef\frontmatter@init{%
654 \global\let\@FMN@list\@empty
655 }%

```

```

656 \def\frontmatter@footnotemark#1{%
657 \leavevmode
658 \ifhmode\edef\@x@sf{\the\spacefactor}\nobreak\fi
659 \begingroup
660 \hyper@linkstart {link}{frontmatter.#1}%
661 \csname c@\@mpfn\endcsname#1\relax
662 \def\@thefnmark{\frontmatter@thefootnote}%
663 \@makefnmark
664 \hyper@linkend
665 \endgroup
666 \ifhmode\spacefactor\@x@sf\fi

```

```
667 \relax
668 }%
```

9.4 The keywords command

`\keywords` Usual game, save text in a macro for processing by `\maketitle`.

```
\@keywords 669 \def\keywords#1{%
670   \aftermaketitle@chk{\keywords}%
671   \gdef\@keywords{#1}%
672 }%
673 \appdef\frontmatter@init{%
674   \let\@keywords\@empty
675 }%
```

9.5 The `\date` command and related commands

`\date` Use the `\date` command to specify the document date, the `\received` command to specify the date received, `\revised` for date revised, `\accepted` for date accepted, `\revised` and `\published` for date published. Normally only `\date` to be used by author, `\accepted` the remainder used only by editors.

`\published` DPC: As for `\keywords`, but this time don't flag a warning if there is no revision date specified.

`\@date` In each case the user-level command defines the value of a macro which buffers the data entered by the user. For instance, `\received` causes `\@received` to acquire a value. The optional argument allows the user to override the text that will be typeset along with the date; the default value of that text is itself a localized macro.

```
676 \newcommand*\frontmatter@date[2][\Dated@name]{\def\@date{#1#2}}%
677 \def\@date{}%
678 \newcommand*\received[2][\Received@name]{\def\@received{#1#2}}%
679 \def\@received{}%
680 \newcommand*\revised[2][\Revised@name]{\def\@revised{#1#2}}%
681 \def\@revised{}%
682 \newcommand*\accepted[2][\Accepted@name]{\def\@accepted{#1#2}}%
683 \def\@accepted{}%
684 \newcommand*\published[2][\Published@name]{\def\@published{#1#2}}%
685 \def\@published{}%
```

9.6 The pacs command

PACS, the Physics and Astronomy Classification Scheme.

`\pacs` As for `\keywords`

```
\@pacs 686 \def\pacs#1{%
687   \aftermaketitle@chk{\pacs}%
688   \gdef\@pacs{#1}%
689 }%
690 \appdef\frontmatter@init{%
```

```
691 \let\@pacs\@empty
692 }%
```

9.7 The `\preprint` command

```
693 \def\preprint#1{\gappdef\@preprint{\preprint{#1}}}%
694 \appdef\frontmatter@init{%
695 \let\@preprint\@empty
696 }%
```

9.8 The abstract environment

`\absbox`

```
697 \newbox\absbox
```

abstract Abstract, as in AMS classes, must be specified *before* `\maketitle`. It just saves everything up in `\absbox`. Note that the specifics of how the abstract is to be formatted are set by `\frontmatter@abstractwidth`, `\frontmatter@abstractheading`, and `\frontmatter@abstractfont`.

Here we wish to set the abstract into type but save it away in a box, much like the `\minipage` command does.

Note that the `\endabstract` portion of the environment begins with code that mostly duplicates `\endminipage`, but without the `\@iiparbox`. At the end, we simply transfer the contents of the `\minipage` into a box of our own.

However, we also have to end the gratuitous paragraph begun by `\minipage`. We ensure that no trace of that paragraph is left, by absorbing the `\parindent` box. Doing so destroys the paragraph entirely, except for the `\parskip` glue, and that morsel is pruned, because we are at the top of a page.

This mechanism is vulnerable, however, because anything placed into the horizontal list after the `\parindent` box will confound it. And that is exactly what happens under MikTeX: There seems to be an extension to the TeX standard operating here which inserts a `\special` at the beginning of every paragraph. (The mechanism is *not* based on `\everypar`.)

To accommodate this state of affairs, we have a new mechanism that offers an even more complete rewrite of `\minipage`.

Note that an entry is made in the toc for the abstract; this has the side effect of creating a PDF bookmark for this element if the `hyperref` package is in effect.

```
698 \def\toclevel@abstract{1}%
699 \def\addcontents@abstract{%
700 \phantomsection
701 \expandafter\def\csname Parent0\endcsname{section*.2}%
702 \expandafter\@argswap@val\expandafter{\abstractname}{\addcontentsline{toc}{abstract}}%
703 }%
704 \newenvironment{frontmatter@abstract}{%
705 \aftermaketitle@chk{\begin{abstract}}%
706 \global\setbox\absbox\vbox\bgroup
707 \color@begingroup
```

```

708 \columnwidth\textwidth
709 \hsize\columnwidth
710 \@parboxrestore

```

The following line switches footnotes to the mpfootnote series. This action should rather be taken by `\frontmatter@abstractfont`, which can be customized. There is also an interaction with `\mini@note`.

```

711 \def\@mpfn{mpfootnote}\def\thempfn{\thempfootnote}\c@mpfootnote\z@
712 \let\@footnotetext\frontmatter@footnotetext
713 \minipagefootnote@init
714 \let\set@listindent\set@listindent@
715 \let\@listdepth\@mplistdepth \@mplistdepth\z@
716 \let\@environment{description}{frontmatter@description}%
717 \@minipagerestore
718 \@setminipage
719 \frontmatter@abstractheading
720 \frontmatter@abstractfont
721 \let\footnote\mini@note
722 \expandafter\everypar\expandafter{\the\everypar\addcontents@abstract\everypar{}}%
723 }{%
724 \par
725 \unskip
726 \minipagefootnote@here
727 \@minipagefalse %% added 24 May 89
728 \color@endgroup
729 \egroup
730 }%

```

`\frontmatter@footnotetext` We reimplement `\@mpfootnotetext` under a new name (so as not to be overridden by the `hyperref` package) and extend it to accomodate hyperrefs.

Note that this procedure is very like `ltxutil`'s `\mp@footnotetext`, except that it uses `\frontmatter@makefntext` instead of `\@makefntext`.

```

731 \long\def\frontmatter@footnotetext#1{%
732 \minipagefootnote@pick
733 \set@footnotefont
734 \set@footnotewidth
735 \@parboxrestore
736 \protected@edef\@currentlabel{\csname p@\@mpfn\endcsname\@thefnmark}%
737 \color@begingroup
738 \frontmatter@makefntext{%
739 \rule\z@\footnotesep\ignorespaces#1\@finalstrut\strutbox\vadjust{\vskip\z@skip}%
740 }%
741 \color@endgroup
742 \minipagefootnote@drop
743 }%

```

`\ltx@no@footwarn`

```

744 \def\ltx@no@footnote{%
745 \let\ltx@xfootnote\ltx@no@xfootnote\let\ltx@yfootnote\ltx@no@yfootnote

```

```

746 \let\ltx@xfootmark\ltx@no@xfootmark\let\ltx@yfootmark\ltx@no@yfootmark
747 \let\ltx@xfoottext\ltx@no@xfoottext\let\ltx@yfoottext\ltx@no@yfoottext
748 }%
749 \def\ltx@no@xfootnote[#1]#2{\ltx@no@footwarn\footnote}%
750 \def\ltx@no@yfootnote#1{\ltx@no@footwarn\footnote}%
751 \def\ltx@no@xfootmark[#1]{\ltx@no@footwarn\footnotemark}%
752 \def\ltx@no@yfootmark{\ltx@no@footwarn\footnotemark}%
753 \def\ltx@no@xfoottext[#1]#2{\ltx@no@footwarn\footnotetext}%
754 \def\ltx@no@yfoottext#1{\ltx@no@footwarn\footnotetext}%
755 \def\ltx@no@footwarn#1{%
756 \class@warn{%
757 The \string#1\space command is not legal on the title page;
758 using \string\thanks\space instead might suit you: consult the manual for details%
759 }%
760 }%

```

`\frontmatter@abstractheading` The default abstract head; journals will override this procedure.

```

761 \def\frontmatter@abstractheading{%
762 \begingroup
763 \centering\large
764 \abstractname
765 \par
766 \endgroup
767 }%

```

`\frontmatter@abstractfont` The default type specification for the body of the abstract. Journals will override this setting.

```

768 \def\frontmatter@abstractfont{}%

```

`frontmatter@description` Within the abstract, the description environment is defined as follows:

```

769 \newenvironment{frontmatter@description}{%
770 \list{}{%
771 \leftmargin\z@
772 \labelwidth\z@

% \itemindent-\leftmargin
%

773 \itemindent\z@
774 \let\makelabel\frontmatter@descriptionlabel
775 }%
776 }{%
777 \endlist
778 }%
779 \def\frontmatter@descriptionlabel#1{%
780 \hspace\labelsep
781 \normalfont\bfseries
782 #1:%
783 }%

```

`\frontmatter@abstractwidth` The default setting is the full text width; journals can override this setting.

```
784 \def\frontmatter@abstractwidth{\textwidth}
```

`\frontmatter@abstract@produce` This procedure determines how the abstract is incorporated into the title block. We split this out in anticipation of the need to lift the limitation that the abstract not break over pages.

If we are in preprint style, we provide an easy pagebreak point immediately above the abstract. This means that the abstract will either fit entirely on the same page as the title block, or it will start a page of its own (which may itself break onto a subsequent page if necessary).

```
785 \def\frontmatter@abstract@produce{%
786   \par
787   \preprintsty@sw{%
788     \do@output@MVL{%
789       \vskip\frontmatter@preabstractspace
790       \vskip200\p@\@plus1fil
791       \penalty-200\relax
792       \vskip-200\p@\@plus-1fil
793     }%
794   }{%
795     \addvspace{\frontmatter@preabstractspace}%
796   }%
797   \begingroup
798   \dimen@baselineskip
799   \setbox\z@\vtop{\unvcopy\absbox}%
800   \advance\dimen@-\ht\z@\advance\dimen@-\prevdepth
801   \@ifdim{\dimen@>\z@}{\vskip\dimen@}{}%
802   \endgroup
803   \begingroup
804   \prep@absbox
805   \unvbox\absbox
806   \post@absbox
807   \endgroup
808   \@ifx{\@empty\mini@notes}{\mini@notes\par}%
809   \addvspace\frontmatter@postabstractspace
810 }%
811 \appdef\frontmatter@init{\let\mini@notes\@empty}%
812 \let\prep@absbox\@empty
813 \let\post@absbox\@empty
```

`\frontmatter@preabstractspace` Space above and space below abstract in title block

```
814 \def\frontmatter@preabstractspace{.5\baselineskip}
```

```
815 \def\frontmatter@postabstractspace{.5\baselineskip}
```

9.9 Formatting the title block

`titlepage` This is L^AT_EX 2_ε's article class version, with modifications.

```
816 \newenvironment{frontmatter@titlepage}{%
```

```

817     \twocolumn@sw{\onecolumngrid}{\newpage}%
818     \thispagestyle{titlepage}%
819     \setcounter{page}\@ne
820 }{%
821     \twocolumn@sw{\twocolumngrid}{\newpage}%
822     \twoside@sw}{{%
823         \setcounter{page}\@ne
824     }%
825 }%

```

`\maketitle` Put it all together to format the title block.

Gotcha! If you expand `\csnameundefined\endcsname`, you change the meaning of `\undefined` from “Undefined” to `\relax`. Watchout!

```

826 \def\frontmatter@maketitle{%
827     \@author@finish
828     \title@column\titleblock@produce
829     \suppressfloats[t]%

```

Now save some memory.

```

830     \let\and\relax
831     \let\affiliation@gobble
832     \let\author@gobble
833     \let@AAC@list@empty
834     \let@AFF@list@empty
835     \let@AFG@list@empty
836     \let@AF@join@AF@join@error
837     \let@email@gobble
838     \let@address@empty
839     \let\maketitle\relax
840     \let\thanks@gobble
841     \let\abstract@undefined\let\endabstract@undefined
842     \titlepage@sw{%
843         \vfil
844         \clearpage
845     }{%
846 }%

```

`\maketitle@Hy` We provide the means to take back the definition of `\maketitle` from `hyperref`: we do not need its help in providing hypertext services in the title page.

```

847 \def\maketitle@Hy{%
848     \let\Hy@saved@footnotemark@footnotemark
849     \let\Hy@saved@footnotetext@footnotetext
850     \let@footnotemark\H@footnotemark
851     \let@footnotetext\H@footnotetext
852     \ifnextchar [%]
853         \Hy@maketitle@optarg
854     {%
855         \HyOrg@maketitle
856         \Hy@maketitle@end
857     }%

```

```

858 }%
859 \appdef\class@documenthook{%
860   \@ifx{\maketitle\maketitle@Hy}{%
861     \class@info{Taking \string\maketitle\space back from hyperref}%
862     \let\maketitle\frontmatter@maketitle
863   }{%
864   }%
865 }%

```

`\titleblock@produce` This procedure produces the title block.

It effectively executes inside a group and always returns us to vertical mode.

Note: we assume that it is OK to set the footnote counter to zero at this point.

Is this a safe assumption?

```

866 \def\titleblock@produce{%
867   \begingroup

```

First, we restore the footnote mechanism to its default state, then we customize the way the footnote mark is produced and how it is formatted.

```

868   \ltx@footnote@pop

```

The following three lines establish an independent footnote counter for use in the title block.

```

869   \def\@mpfn{mpfootnote}%
870   \def\thempfn{\thempfootnote}%
871   \c@mpfootnote\z@
872   \let\@makefnmark\frontmatter@makefnmark
873   \frontmatter@setup
874   \thispagestyle{titlepage}\label{FirstPage}%

```

Produce the title:

```

875   \frontmatter@title@produce

```

Produce the author list:

```

876   \groupauthors@sw{%
877     \frontmatter@author@produce@group
878   }{%
879     \frontmatter@author@produce@script
880   }%

```

Produce the dates:

```

881   \frontmatter@RRAPformat{%
882     \expandafter\produce@RRAP\expandafter{\@date}%
883     \expandafter\produce@RRAP\expandafter{\@received}%
884     \expandafter\produce@RRAP\expandafter{\@revised}%
885     \expandafter\produce@RRAP\expandafter{\@accepted}%
886     \expandafter\produce@RRAP\expandafter{\@published}%
887   }%

```

Produce the abstract, PACS, and keywords, and end any paragraph.

```

888   \frontmatter@abstract@produce
889   \@ifx@empty\@pacs{}{%

```



```

890   \@pacs@produce\@pacs
891 }%
892 \@ifx@empty\@keywords{}{%
893   \@keywords@produce\@keywords
894 }%
895 \par
896 \frontmatter@finalspace
897 \endgroup
898 }%

```

`\frontmatter@title@produce` The default formatting procedure for the article title. This procedure should take care of the vertical space below the title.

Clients may override this procedure, but it is more likely that they will use the hooks `\frontmatter@title@above`, `\frontmatter@title@format`, and `\frontmatter@title@below`.

```

899 \def\toclevel@title{0}%
900 \def\frontmatter@title@produce{%
901   \begingroup
902   \frontmatter@title@above
903   \frontmatter@title@format
904   \@title
905   \unskip
906   \phantomsection\expandafter\@argswap@val\expandafter{\@title}{\addcontentsline{toc}{title}}%
907   \@ifx{\@title@aux\@title@aux@cleared}{}{%
908     \expandafter\frontmatter@footnote\expandafter{\@title@aux}%
909   }%
910   \par
911   \frontmatter@title@below
912 \endgroup
913 }%
914 \appdef\let@mark{\let\\\relax}%

```

`\frontmatter@title@above` The default values for formatting specifications for the article title.

`\frontmatter@title@format` The procedure `\frontmatter@title@above` should take care of the vertical space above the title; `\frontmatter@title@below` below. The procedure `\frontmatter@title@format` should invoke any font switches, etc. that may apply to the title.

Journals will override this procedure.

```

915 \def\frontmatter@title@above{}%
916 \def\frontmatter@title@format{}%
917 \def\frontmatter@title@below{\addvspace{\baselineskip}}%

```

9.9.1 Authors and affiliations in superscriptaddress style

`\frontmatter@author@produce@script` `\frontmatter@author@produce@script` is an alias for `\frontmatter@author@produce`, the procedure that formats the author/affiliation list.

In this case, the authors affiliations are being superscripted (class option `superscriptaddress`).

This procedure must ensure that any paragraph that it starts gets ended finally.

```

918 \def\frontmatter@author@produce@script{%
919   \begingroup
920   \let\author@present\@author@present@script
921   \frontmatterverbose@sw{\typeout{\string\frontmatter@author@produce@script:}\say\@AAC@list\s

```

When the author/affiliation list `\@AAC@list` is executed, `\@tempcnt` counts each author, and `\@tempa` stores a list of author indices for the current collaboration.

Note: this procedure uses `\AU@temp` to hold a list of author counts for each collaboration. Note: also uses `\@tempcnta` to communicate between procedures. This usage of `\@tempcnta` is OK, because the expansion of `\@AAC@list` will trigger only the execution of our own procedures.

```

922   \let\AU@temp\@empty
923   \@tempcnta\z@

```

We wish to know how many authors are in each collaboration, for the purposes of `\listcomma` and `\listand`.

Here we assign values for the intercolated operators appearing within `\@AAC@list`, then execute that macro, registering the authors in each collaboration. Afterwards, clean up by emulating an empty collaboration.

The result, stored in `\AU@temp`, is a list of brace-delimited tokens, each a number representing the number of authors in that collaboration.

```

924   \let\AF@opr \@gobble
925   \def\AU@opr{\@author@count\@tempcnta}%
926   \def\CO@opr{\@collaboration@count\AU@temp\@tempcnta}%
927   \@AAC@list
928   \expandafter\CO@opr\@author@cleared

```

Next, present the authors and their affiliations, with the collaborations interleaved.

We assign values for the intercolated operators appearing within `\@AAC@list`. Next, assign `\@listcomma` based on the number of authors in the first collaboration. Then expand `\@AAC@list`.

Upon completion, there will be two space tokens following the last author because of `\listand` processing; remove them, then end the last paragraph.

FIXME: this juncture would be a good time to effectively eliminate the unused affiliations in `\@AFF@list`.

```

929   \begingroup
930   \frontmatter@author@format
931   \let\AF@opr \@affilID@def
932   \let\AU@opr \@author@present
933   \def\CO@opr{\@collaboration@present\AU@temp}%
934   \set@listcomma@list\AU@temp
935   \@AAC@list
936   \unskip\unskip
937   \par
938   \endgroup

```

We now list out the affiliations in the order they appeared.

```

939 \beginngroup
940 \frontmatter@above@affiliation@script
941 \let\AFF@opr \@affil@script
942 \@AFF@list
943 \frontmatter@footnote@produce
944 \par
945 \endgroup
946 \endgroup
947 }%

```

`\@author@count` This version of `\AU@opr` counts the number of authors it processes.

```

948 \def\@author@count#1{%
949 \advance#1\@ne
950 \@author@gobble
951 }%

```

`\@collaboration@present` Format a collaboration. Note that we immediately end the paragraph thus begun, because we only support superscriptaddress-style processing.

Note also that the execution of the production procedures takes place inside of a group; for reasons of protective programming.

Bug note: originally, the number of authors in each collaboration was stored in `\@tempa`, but this exposed us to procedures in our production that modified the meaning of `\@tempa`.

The last action done in this procedure is to assign `\@listcomma` based on the number of authors in the next collaboration.

```

952 \def\@collaboration@present#1#2#3#4{%
953 \par
954 \beginngroup
955 \frontmatter@collaboration@above
956 \@affilID@def{}%
957 \@tempcnta\z@
958 \@author@present-{}{(\ignorespaces#3\unskip)}{#4}%
959 \par
960 \endgroup
961 \set@listcomma@list#1%
962 }%
963 \def\frontmatter@collaboration@above{}%

```

`\@collaboration@count` Simply register each author in this collaboration. Note: `#1` is a `\csname` to hold the value, `#2` is the `\count` register holding the count of interest.

```

964 \def\@collaboration@count#1#2{%
965 \appdef@eval#1{\the#2}#2\z@
966 \@author@gobble
967 }%

```

`\@affilID@def` The `\@affilID@def` procedure, an alias of `\AF@opr` used during `\frontmatter@author@produce@script` processing, memorizes the affiliation in `\@affilID@temp`.

```

968 \def\@affilID@def{\def\@affilID@temp}%

```

`\@affilID@temp` The macro `\@affilID@temp` is used to communicate between `\doauthor` and instances of `\AF@opr` within the author list.

```
969 \let\@affilID@temp\@empty
```

`\affils@present@script` An alias of `\AFG@opr`, this procedure is applied to elements in `\@AFG@list`. It builds `\@AFU@list`, a list of unique affiliations found within affiliation groups.

```

%\def\affils@present@script#1{%
% \get@affil#1{%
%}%
%\def\get@affil#1{%
% \def\@tempa{#1}%
% \ifx{\@empty\@tempa}{}%
% \@booleanfalse\temp@sw
% \def\AF@opr{\x@match\@tempa}%
% \@AFU@list
% \temp@sw}{%
% \appdef\@AFU@list{\AF@opr{#1}}%
% }%
% \get@affil
% }%
%}%
%
```

`\affil@present@script` An alias of `\AF@opr`, this procedure is applied to `\@AFU@list` when formatting the affiliations under `superscriptaddress`. It in turn applies `\affil@script` to `\@AFF@list`, thereby formatting the affiliation associated with this affiliation index.

Note: it traverses the `\@AFF@list` for each entry in the `\@AFU@list`, thereby making this portion of code execute in N^2 time.

```

%\def\affil@present@script#1{%
% \def\@tempa{#1}%
% \begingroup
% \frontmatter@affiliationfont
% \let\AFF@opr \affil@script
% \@AFF@list
% \endgroup
%}%
%
```

`\affil@script` Alias of `\AFF@opr`, this procedure is applied to `\@AFF@list` when formatting the affiliations under `superscriptaddress`. It rejects all entries not matching the affiliation index held in `\@tempa`.

```

970 \def\affil@script#1#2#3{%
971 \def\@tempifx{#1}\@ifx{\@tempifx\@tempa}{%
972 \if@empty{#2}{}%
973 \par
974 \begingroup
```

```

975 \def\@thefnmark{#1}\@makefnmark\ignorespaces
976 #2%
977 \ifempty{#3}{}\frontmatter@footnote{#3}}%
978 \par
979 \endgroup
980 }%
981 }{}%
982 }%

```

`\@affil@script` Alias of `\AFF@opr`: The affiliations are being formatted in the case where affiliations are being superscripted: make a list out of the affiliations with the numbers printed. Society-specific code can change the formatting by overriding the definition of `\frontmatter@affiliationfont`.

A client may choose to set `\affil@cutoff` to either `\@ne` (the default) or `\tw@`. The latter setting will enforce a rule to the effect that if a single affiliation appears on the title page, then no affiliation superscript at all is produced.

- #1—Affiliation ID: a number; zero signifies a `\noaffiliation`.
- #2—Collaboration ID
- #3—Affiliation address
- #4—Auxiliary info

```

983 \def\@affil@script#1#2#3#4{%
    If the affiliation is the \noaffiliation, then we do nothing.
984 \@ifnum{#1=\z@}{}%
985 \par
986 \begingroup
987 \frontmatter@affiliationfont
988 \@ifnum{\c@affil<\affil@cutoff}{}%
989 \def\@thefnmark{#1}\@makefnmark
990 }%
991 \ignorespaces#3%
992 \ifempty{#4}{}\frontmatter@footnote{#4}}%
993 \par
994 \endgroup
995 }%
996 }%
997 \let\affil@cutoff\@ne

```

`\@author@present@script` This version of `\AU@opr` applies to the `superscriptaddress` class option. Need to add commas between groups of address numbers, which are passed in the macro `\@affilID@temp` in the form `{3}{4}{7}` if this set of authors is related to addresses, 3, 4 and 7.

```

998 \def\@author@present@script#1#2#3{%
999 \begingroup
1000 \gdef\comma@space{\textsuperscript{,\,}}%
1001 \doauthor{#2}{#3}{\@affil@present@script}%
1002 \endgroup
1003 \advance\@tempcnta\m@ne
1004 }%

```

```

1005 \def\@affilcomma#1#2{%
1006 \@ifx{\z@#1}{%
1007 \@ifx{\relax#2}{-}{%
1008 \@affilcomma{#2}%
1009 }%
1010 }{%
1011 #1%
1012 \@ifx{\relax#2}{-}{%
1013 \@ifx{\z@#2}{%
1014 \@affilcomma
1015 }{%
1016 ,\,\@affilcomma{#2}%
1017 }%
1018 }%
1019 }%
1020 }%

```

`\@affil@present@script` The `\@affil@present@script` procedure presents the reference to the affiliations in the case of superscript addresses.

The affiliations are presented to `\@affil@present@script@` as a list of brace-delimited tokens, each containing the affiliation ID (a number). The list is terminated by the token `\relax`. The macro recurses (via tail recursion) until the terminating token is encountered. Note that an affiliation ID of zero signifies a `\noaffiliation`: references to the `\noaffiliation` are passed over.

Upon termination, the affiliations, if any, are produced via `\textsuperscript` and the appropriate boolean is queued via `\aftergroup`. The boolean signifies that a non-trivial affiliation was produced, so that the proper punctuation can be produced. The group in question is that opened and closed by the `\doauthor` procedure.

This procedure uses `\@tempa` as a scratch register.

```

1021 \def\@affil@present@script{%
1022 \let\@tempa\@empty
1023 \expandafter\@affil@present@script@\@affilID@temp\relax
1024 }%
1025 \def\@affil@present@script@#1{%
1026 \@ifx{\relax#1}{%
1027 \@ifx{\@tempa\@empty}{%
1028 \aftergroup\false@sw
1029 }{%
1030 \textsuperscript{\expandafter\@affilcomma\@tempa\relax\relax}%
1031 \aftergroup\true@sw
1032 }%
1033 }{%
1034 \@ifnum{#1=\z@}{-}{\appdef\@tempa{#1}}%
1035 \@affil@present@script@
1036 }%
1037 }%
1038 \@provide\@author@parskip{\z@skip}%

```

9.9.2 Authors and affiliations in groupedaddress style

`\frontmatter@author@produce@group` Alias for `\frontmatter@author@produce` when `groupedaddress` is in effect, the procedure that formats the author/affiliation list.

In this case, the authors are being grouped above their shared addresses. How it works: the `\@AFG@list`, a list of all unique affiliation groups, is expanded. For each such group, all authors belonging to that group are formatted above the affiliation group. Collaborations are silently passed over.

This procedure must ensure that any paragraph that it starts gets ended finally.

```

1039 \def\frontmatter@author@produce@group{%
1040   \begingroup
1041     \let\@author@present\@author@present@group
1042     \frontmatter@authorformat
1043     \frontmatterverbose@sw{\typeout{\string\frontmatter@author@produce@group:}\say\@AAC@list\sa
1044     \let\AU@temp\@empty
1045     \set@listcomma@list\AU@temp
1046     \def\CO@opr{\@collaboration@present\AU@temp}%
1047     \let\AFG@opr \affils@present@group
1048     \let\@listcomma\relax
1049     \@AFG@list
1050     \frontmatter@footnote@produce
1051     \par
1052   \endgroup
1053   \frontmatter@authorbelow
1054 }%
1055 \@provide\frontmatter@authorbelow{}%

```

`\affils@present@group` Alias of `\AFG@opr`, this procedure is used on every element of `\@AFG@list`, the list of unique affiliation groups, when formatting the author/affiliation block: It presents all authors sharing this affiliation group.

This procedure is called via the procedure `\frontmatter@author@produce@group`, an alias for `\frontmatter@author@produce`,

Its use pertains to the class options `groupedaddress`, `unsortedaddress`, and `runinaddress` (that is, `\groupauthors@sw` is true).

For each invocation, the entire `\@AAC@list` is run through (twice), making this process execute in N^2 time. (Is this really true?)

```

1056 \def\affils@present@group#1{%

```

Count (using `\@tempcnta`) the authors in the author list whose affiliation group matches the argument `#1`.

Note that `\AF@temp` is used as a storage register for the argument of the procedure, for purposes of comparison using `\ifx`.

Note: here we use `\@tempcnta` to accumulate the number of authors in the current affiliation set.

QUERY: do the value of `\AF@temp` and `\AF@opr` need to persist?

QUERY: what value does `\AU@opr` have at this point? ANSWER: the `\@affilID@count` and `\@affilID@match` procedures assign meanings to `\AU@opr`

and \CO@opr dynamically. We initialize the two operators to \@undefined so as to catch the pathological cases.

```

1057 \begingroup
1058   \def\AF@temp{#1}%
1059   \@tempcnta\z@
1060   \let\AU@opr \@undefined
1061   \let\CO@opr \@undefined
1062   \def\AF@opr{\@affilID@count\AF@temp\@tempcnta}%
1063   \@AAC@list

```

If there are no authors using this affiliation group, skip it.

```

1064   \ifnum{\@tempcnta=\z@}{-}{%

```

DPC: If we have a list of length two, need to locally zap a comma.

```

1065     \begingroup
1066     \frontmatter@above@affilgroup
1067     \set@listcomma@count\@tempcnta

```

Run through the author list, presenting (with \@author@present) those authors whose affiliation matched the given one.

```

1068     \let\AU@opr \@undefined
1069     \let\CO@opr \@undefined
1070     \def\AF@opr{\@affilID@match\AF@temp}%
1071     \@AAC@list
1072   \endgroup

```

Now that the authors have all been presented, present the affiliations, grouped.

Note: \@tempcnta is the number of affiliations for this set of authors.

```

1073   \begingroup
1074   \par
1075   \frontmatter@above@affiliation
1076   \frontmatter@affiliationfont
1077   \let\\frontmatter@addressnewline
1078   \@tempcnta\z@
1079   \@tfor\AF@temp:=#1\do{%
1080     \expandafter\@ifx\expandafter{\expandafter\z@\AF@temp}{-}{%
1081       \advance\@tempcnta\@ne
1082     }%
1083   }%
1084   \@ifnum{\@tempcnta=\tw@}{%
1085     \let\@listcomma\relax
1086   }{}%
1087   \def@after@address
1088   \runinaddress@sw{%
1089     }{%
1090     \tightenlines@sw}{%

```

The following line determines the space between affiliations in grouped mode

```

1091     \parskip\z@
1092   }%
1093   \appdef\after@address\par

```



```

1094     }%
1095     \let\AFF@opr \@affil@group
1096     \do@affil@fromgroup\@AFF@list#1\relax
1097     \endgroup
      End of branch handling authors.
1098     }%
1099     \par
1100 \endgroup
1101 }%

```

`\def@after@address` Each of these procedures assigns a meaning to `\after@address`, the first a useful default, the second a nil. A society or journal substyle may define it according to its own requirements.

```

1102 \def\def@after@address{\def\after@address{\@listcomma\ \@listand}}%
1103 \def\def@after@address@empty{\let\after@address\@empty}%

```

`\@affilID@count` The control sequence name `\AF@opr` is placed in the author/affiliation list (`\@AAC@list`) for each (new) affiliation, with that affiliation as its argument.

The control sequence name `\AF@opr` is an alias of a procedure to count the number of authors at a given affiliation (`\@affilID@count`) or to present the given authors (`\@affilID@match`). These two procedures are executed when formatting under the `groupedaddress` class option.

```

1104 \def\@affilID@count#1#2#3{%
1105   \def\@tempifx{#3}%
1106   \@ifx{\@tempifx#1}{%
1107     \def\AU@opr{\@author@count#2}%
1108   }{%
1109     \let\AU@opr \@author@gobble
1110   }%
1111   \let\C0@opr \@collaboration@gobble
1112 }%
1113 \def\@affilID@match#1#2{%
1114   \def\@tempifx{#2}%
1115   \@ifx{\@tempifx#1}{%
1116     \let\AU@opr \@author@present
1117   }{%
1118     \let\AU@opr \@author@gobble
1119   }%
1120   \let\C0@opr \@collaboration@gobble
1121 }%

```

`\do@affil@fromgroup` Executes iteratively: selects the next address ID to print, and then re-execute the list of addresses to print the text of that address.

Note: an argument of `\relax` breaks out of this iteration, while an argument of `\z@` (`\noaffiliation`) is a no-op.

Note: we have created an N^2 computing process. FIXME: can use hashing instead, you know.

```

1122 \def\do@affil@fromgroup#1#2{%
1123   \@ifx{\relax#2}{-}{%
1124     \count@#2\relax
1125     \@ifnum{\z@=\count@}{-}{#1}%
1126     \do@affil@fromgroup#1%
1127   }%
1128 }%

```

`\@affil@group` The alias of `\AFF@opr` when the list `\@AFF@list` is executed by `\do@affil@fromgroup` (`groupedaddress`): Print the address if its number matches `\count@` (value set by `\do@affil@fromgroup`).

Note that we detect a `\noaffiliation` here by the affiliation address being the same as the expansion of `\blankaffiliation`.

I made a mistake when coding the comparison to `\blankaffiliation`: it originally read `\@ifx{#3\blankaffiliation}`. This is obviously wrong once you think twice.

```

1129 \def\@affil@group#1#2#3#4{%
1130   \@ifnum{#1=\count@}{-%
1131     \def\@tempa{#3}%
1132     \@ifx{\@tempa\blankaffiliation}{-}{-%
1133       #3%
1134       \@ifempty{#4}{-}{-%
1135         \frontmatter@footnote{#4}%
1136       }%
1137       \after@address
1138     }%
1139     \advance\@tempcnta\m@ne
1140   }-}{-%
1141 }%

```

`\@author@present@group` This version of `\AU@opr` applies to the `groupedaddress` class option and its ilk.
`\@affil@present@group` Traverse the list calling the `\doauthor` hook on each author.

The third argument of `\doauthor` fulfills the requirement that it queue up a boolean via `\aftergroup`.

```

1142 \def\@author@present@group#1#2#3{%
1143   \gdef\comma@space{\gdef\comma@space{\textsuperscript{,\,}}}%
1144   \doauthor{#2}{#3}{\@affil@present@group}%
1145   \advance\@tempcnta\m@ne
1146 }%
1147 \def\@affil@present@group{%
1148   \aftergroup\false@sw
1149 }%

```

`\@pacs@produce` PACS, keywords and dates.

```

1150 \def\@pacs@produce#1{%
1151   \showPACS@sw{%
1152     \begingroup
1153     \frontmatter@PACS@format

```

```

1154   \@pacs@name#1\par
1155   \endgroup
1156 }{%
1157   \@if@empty{#1}{-}{%
1158     \class@warn{\PACS@warn}%
1159   }%
1160 }%
1161 }%
1162 \def\PACS@warn{If you want your PACS to appear in your output, use document class option showpa

```

\@keywords@produce

```

1163 \def\@keywords@produce#1{%
1164   \showKEYS@sw{%
1165     \begingroup
1166     \frontmatter@keys@format
1167     \@keys@name#1\par
1168     \endgroup
1169   }{%
1170     \@if@empty{#1}{-}{%
1171       \class@warn{If you want your keywords to appear in your output, use document class option sh
1172     }%
1173   }%
1174 }%

```

\@frontmatter@footnote@produce@footnote
\@frontmatter@footnote@produce@endnote

Produce any footnotes to appear at the bottom of the title page.
If frontmatter footnotes have been redirected to the bibliography, this will be
a no-op. ref.: \present@bibnote.

```

1175 \def\frontmatter@footnote@produce@footnote{%
1176   \let\@TBN@opr\present@FM@footnote
1177   \@FMN@list
1178   \global\let\@FMN@list\@empty
1179 }%

1180 \def\present@FM@footnote#1#2{%
1181   \begingroup
1182   \csname c@\@mpfn@endcsname#1\relax
1183   \def\@thefnmark{\frontmatter@thefootnote}%
1184   \frontmatter@footnotetext{#2}%
1185   \endgroup
1186 }%
1187 \def\frontmatter@footnote@produce@endnote{%
1188 }%

```

10 Package defaults

\@title@column We give meanings to the Booleans and other macros that a client document class
\@preprintsty@sw would set on our behalf.

```

\@collaboration@sw 1189 \appdef\frontmatter@init{%
\@frontmatter@footnote@produce
\@do@output@MVL
\@comma@space

```

```

1190 \@ifxundefined\title@column      {\let\title@column\@empty}{}%
1191 \@ifxundefined\preprintsty@sw    {\@booleanfalse\preprintsty@sw}{}%
1192 \@ifxundefined\frontmatter@footnote@produce{\let\frontmatter@footnote@produce\frontmatter@footnote@produce}{}%
1193 \@ifxundefined\do@output@MVL     {\let\do@output@MVL\@firstofone}{}%
1194 \@ifxundefined\comma@space      {\let\comma@space\@empty}{}%
1195 }%

```

`\frontmatter@thefootnote` In the title block, the footnote symbol (used for alternate affiliation and sundry) is a `\@fnsymbol` or a lowercase letter, as selected by a boolean. The society or journal may override this definition.

```

1196 \def\frontmatter@thefootnote{%
1197 \altaffilletter@sw{\@alph}{\@fnsymbol}{\csname c@\@mpfn\endcsname}%
1198 }%
1199 \@ifx{\altaffilletter@sw\@undefined}{\@booleantrue\altaffilletter@sw}{}%

```

`\frontmatter@makefnmark` The default procedure for setting the footnote mark within the frontmatter. A client may override this procedure.

```

1200 \def\frontmatter@makefnmark{%
1201 \@textsuperscript{%
1202 \normalfont\@thefnmark
1203 }%
1204 }%

```

`\frontmatter@makefntext` This procedure is used when setting footnotes within the title block.

Note that we are `hyperref` friendly: we invoke `\Hy@raisedlink` so that this footnote becomes a hypertext anchor. If `hyperref` is not loaded, then `ltxutil` has our act covered via some stubs.

```

1205 \long\def\frontmatter@makefntext#1{%
1206 \parindent 1em
1207 \noindent
1208 \Hy@raisedlink{\hyper@anchorstart{\frontmatter.\expandafter\the\csname c@\@mpfn\endcsname}\hyphenchar\font{-1}}
1209 \@makefnmark
1210 #1%
1211 }%

```

`\frontmatter@setup` The default type specification for the title page. Clients will override this definition.

```

1212 \def\frontmatter@setup{}%

```

`\frontmatter@RRAPformat` The procedure `\frontmatter@RRAPformat` is the formatting procedure for the “Received, Revised, etc.” block on the title page. The macro `\punct@RRAP` produces the punctuation between the entries. Clients will override these two definitions.

The procedure `\produce@RRAP` is fairly general, and should be used by most journal substyles.

The procedure `\frontmatter@RRAP@format` will be overridden by the journal.

```

1213 \def\frontmatter@RRAPformat#1{%
1214 \removelastskip

```

```

1215 \begingroup
1216 \frontmatter@RRAP@format
1217 #1\par
1218 \endgroup
1219 }%
1220 \def\punct@RRAP{; }%
1221 \def\produce@RRAP#1{%
1222 \if@empty{#1}-}%
1223 \@ifvmode{\leavevmode}{\unskip\punct@RRAP\ignorespaces}%
1224 #1%
1225 }%
1226 }%

```

`\frontmatter@authorformat` The default type specification for the author list. Clients will override this definition. For one alternative, see the `revtex4` document class.

```
1227 \def\frontmatter@authorformat{}%
```

`\frontmatter@above@affilgroup` The default amount of space above an affiliation group (in a `\affils@present@group` production). Clients will override this definition.

```
1228 \def\frontmatter@above@affilgroup{}%
```

`\frontmatter@above@affiliation` The `\frontmatter@above@affiliation` is the amount of space above affiliations in the `groupedaddress` style, and `\frontmatter@above@affiliation@script` is that for `superscriptaddress`. Clients will override this definition. For one alternative, see the `revtex4` document class.

```
1229 \def\frontmatter@above@affiliation{}%
```

```
1230 \def\frontmatter@above@affiliation@script{}%
```

`\frontmatter@affiliationfont` The default type specification for the affiliation. Clients will override this definition. For one alternative, see the `revtex4` document class, where several alternative definitions are made.

```
1231 \def\frontmatter@affiliationfont{\itshape\selectfont}%
```

`\frontmatter@RRAP@format` The default type specification for the dates. Clients will override this definition.

```
1232 \def\frontmatter@RRAP@format{}%
```

`\frontmatter@PACS@format` Specify the formatting of the title page PACS statement. Journals will override.

```
1233 \def\frontmatter@PACS@format{}%
```

`\frontmatter@keys@format` Specify the formatting of the title page keywords statement. Journals will override.

```
1234 \def\frontmatter@keys@format{}%
```

`\frontmatter@finalspace`

```
1235 \def\frontmatter@finalspace{\addvspace{18\p@}}
```

`\frontmatter@addressnewline` The definition of `\\` for address handling. Default puts all the ‘lines’ on a run-in line, separated by comma and space. DPC: was space between lines of addresses.

```
1236 \def\frontmatter@addressnewline{%
1237   \@ifhmode{\skip@\lastskip\unskip\unpenalty\break\hskip\skip@}{}%
1238   % was: \vskip-.5ex
1239 }%
```

`\frontmatter@preabstractspace` Space above and space below abstract in title block

```
\frontmatter@postabstractspace 1240 \def\frontmatter@preabstractspace{5.5\p@}
1241 \def\frontmatter@postabstractspace{6.5\p@}
```

`\aftermaketitle@chk` Error-checking code.

```
1242 \def\aftermaketitle@chk#1{%
1243   \@ifx{\maketitle\relax}{%
1244     \class@err{\protect#1 must be used before \protect\maketitle}%
1245   }{}}%
1246 }%
```

`\ps@titlepage` Default page style for title page. Journals will override this procedure.

```
1247 \def\ps@titlepage{\ps@empty}%
```

FIXME: there is a limitation to the default meaning of `\@startpage`: the label “FirstPage” is only defined if the document has a `\maketitle` command.

```
1248 \def\volumeyear#1{\gdef\@volumeyear{#1}}%
1249 \def\@volumeyear{}%
1250 \def\volumenumber#1{\gdef\@volumenumber{#1}}%
1251 \def\@volumenumber{}%
1252 \def\issuenummer#1{\gdef\@issuenummer{#1}}%
1253 \def\@issuenummer{}%
1254 \def\eid#1{\gdef\@eid{#1}}%
1255 \def\@eid{}%
1256 %
1257 \def\startpage#1{\gdef\@startpage{#1}\c@page#1\relax}%
1258 \def\@startpage{\pageref{FirstPage}}%
1259 \def\endpage#1{\gdef\@endpage{#1}}%
1260 \def\@endpage{\pageref{LastPage}}%
```

10.1 Printing out the “list-of” elements

FIXME: The `\appendix@toc` procedure should change the meaning of `\l@section` so that the `\sections` can be appropriately formatted, reflecting their status as appendices.

```
1261 \def\print@toc#1{%
1262   \begingroup
1263   \expandafter\section
1264   \expandafter*%
1265   \expandafter%
```

```

1266             \csname#1name\endcsname
1267             }%
1268 \let\appendix\appendix@toc
1269 \@starttoc{#1}%
1270 \endgroup
1271 }%
1272 \def\appendix@toc{%

```

`\Dated@name` These strings are used in the `\date`, et al. commands.

```

\Received@name 1273 \def\Dated@name{Dated }%
\Revised@name 1274 \def\Received@name{Received }%
\Accepted@name 1275 \def\Revised@name{Revised }%
\Published@name 1276 \def\Accepted@name{Accepted }%
1277 \def\Published@name{Published }%

```

Two commands require robustifying against harsh treatment when TOC entries are written out. Note that `\class@warn` is not user-level markup, but crops up when the `\title` command is missing from the document.

```

1278 \appdef\robustify@contents{%
1279 \let\thanks@gobble\let\class@warn@gobble
1280 \def\begin{string\begin}\def\end{string\end}%
1281 }%

```

10.2 Syntax switch

Shall we take over the syntax of L^AT_EX? By default, Yes, unless the Boolean below has already been defined. In the package version, this is controlled by an option; in the kernel version, the Boolean remains undefined.

`\maketitle` presents a complication. If this code will execute under `ltxgrid`, then its version of the procedure will do fine.

As a package, under `article`, things are different. In this case, what should be done depends upon `\if@titlepage`. If true, then just execute `\maketitle` as it stands. If false, then the `article` class has defined its wrapper procedure, and we should take over the meaning of `\@maketitle` instead.

Here is a list of the commands defined by this package that potentially override those of standard L^AT_EX: `\frontmatter@title`, `\frontmatter@author`, `\frontmatter@and`, `\frontmatter@thanks`, `\frontmatter@date`, `frontmatter@abstract`, `frontmatter@titlepage`, `\frontmatter@maketitle`.

The following code will perform that override, given the appropriate state of the Boolean.

```

1282 \@ifundefined\frontmatter@syntax@sw{\@booleantrue\frontmatter@syntax@sw}{}%
1283 \frontmatter@syntax@sw{%
1284 \let\title \frontmatter@title
1285 \let\author \frontmatter@author
1286 \let\date \frontmatter@date
1287 \@ifundefined\@maketitle{%
1288 \let\maketitle \frontmatter@maketitle
1289 \@booleantrue \titlepage@sw

```

```

1290 }{%
1291 \let\@maketitle \frontmatter@maketitle
1292 \prepdef\maketitle\@author@finish
1293 }%
1294 \let\noaffiliation \frontmatter@noaffiliation
1295 \let\thanks@latex \thanks
1296 \let\thanks \frontmatter@thanks
1297 \let\and@latex \and
1298 \let\and \frontmatter@and
1299 \let@environment{titlepage}{frontmatter@titlepage}%
1300 \let@environment{abstract}{frontmatter@abstract}%
1301 }{%
1302 \let\noaffiliation\@empty
1303 }%

```

10.3 End of the ltxfront kernel

The kernel portion of the ltxfront package is complete.

```
1304 %</kernel>
```

10.4 Remainder of the ltxfront package

Include any code here that ought to be incorporated into the package, but should not be part of the kernel.

```
1305 %<*package>
```

Define formatting as like as possible to the article class. Comands that prepare for \maketitle: \author, \title, \date.

Argument of the above three may contain \\ and \thanks; argument of \author may contain \and. The \\ may still work fine; \and will be ignored (warning); \thanks even though it should not reside in the argument, will work.

An explicit \footnoteshould be treated as if it were \thanks.

```

% \@maketitle: \frontmatter@footnote@produce
%

```

```

1306 \def\thanks@latex#1{%
1307 \footnotemark
1308 \expandafter\expandafter
1309 \expandafter\gappdef
1310 \expandafter\expandafter
1311 \expandafter\@thanks
1312 \expandafter\expandafter
1313 \expandafter{%
1314 \expandafter\expandafter
1315 \expandafter\footnotetext
1316 \expandafter\expandafter
1317 \expandafter[%

```



```

1318 \expandafter\the\csname c@\mpfn\endcsname]{{#1}}%
1319 }%
1320 \@booleanfalse\altaffilletter@sw
1321 \@if@sw@if@titlepage\fi{\@booleantrue}{\@booleanfalse}\titlepage@sw
1322 \def\frontmatter@title@above{\newpage\null\vskip2em\relax}%
1323 \def\frontmatter@title@format{\centering\LARGE\let\thanks\thanks@latex}%
1324 \def\frontmatter@title@below{\vskip1.5em\relax}%
1325 \def\frontmatter@author@format{\centering\large\advance\baselineskip\p@\parskip1.5\p@\let\thank
1326 \def\frontmatter@author@below{\vskip 1em\relax}%
1327 \def\frontmatter@above@affiliation{}%
1328 \def\frontmatter@above@affiliation@script{}%
1329 \def\frontmatter@affiliationfont{\centering\itshape}%
1330 \def\frontmatter@RRAP@format{\centering\large}%
1331 \def\frontmatter@preabstractspace{1.5em}%

1332 \long\def\frontmatter@footnotetext{%
1333 \expandafter\expandafter
1334 \expandafter\footnotetext
1335 \expandafter\expandafter
1336 \expandafter[%
1337 \expandafter\the\csname c@\mpfn\endcsname]%
1338 }%
1339 \def\and@space{\}%
1340 \def\andname{and}%

```

Implement the feature of the article class whereby there is a default `\@date`, left over from the \LaTeX kernel. This package does not have a default date. The user must put in an explicit command, like `\date{\today}`, which will restore \LaTeX 's default behavior.

What if the abstract environment falls after the `\maketitle` command? The environment will be undefined; the user will have to deal with this.

End of the package.

```
1341 %</package>
```

Here ends the programmer's documentation.

Index

Symbols

- \% 556
- \, 380, 1000, 1016, 1143
- .dtx 4
- \@AAC@list . 26–28, 31, 42, 47, 49
- \@AAC@list 502, 503, 508–510, 527, 536, 538, 833, 921, 927, 935, 1043, 1063, 1071
- \@AF@join 29
- \@AF@join 276, 316, 392, 546, 563, 568, 574, 577, 836
- \@AF@join@error .. 547, 549, 836
- \@AFF@list . 24, 25, 28, 42, 44, 50
- \@AFF@list .. 428, 453, 538, 834, 921, 942, 1043, 1096
- \@AFG@list 25–28, 44, 47
- \@AFG@list 504, 521, 523, 524, 528, 536, 538, 835, 921, 1043, 1049
- \@AFU@list 44
- \@FMN@list 32, 33
- \@FMN@list . 634, 651, 654, 1177, 1178
- \@TBN@opr 32
- \@TBN@opr 633, 651, 1176
- \@accepted 676, 885
- \@address 838
- \@affil 23–25, 30
- \@affil .. 408, 411, 413, 415, 418, 420, 426, 431, 442, 452
- \@affil@addr@def 426, 463
- \@affil@aux@def 431, 466
- \@affil@cleared 402
- \@affil@def 23
- \@affil@def 393, 402
- \@affil@group 28
- \@affil@group 1095, 1129
- \@affil@init 23, 24
- \@affil@init 402, 460
- \@affil@join 392, 402
- \@affil@join@ 402
- \@affil@match 24, 25, 28
- \@affil@match 427, 473
- \@affil@nil 24
- \@affil@nil 402, 442
- \@affil@none 367, 398, 402
- \@affil@present@group 32
- \@affil@present@group ... 1142
- \@affil@present@script . 31, 46
- \@affil@present@script .. 1001, 1021
- \@affil@present@script@ ... 46
- \@affil@present@script@ . 1021
- \@affil@script 31
- \@affil@script 941, 983
- \@affilID@count 47, 49
- \@affilID@count 1062, 1104
- \@affilID@def 43
- \@affilID@def 931, 956, 968
- \@affilID@match 47, 49
- \@affilID@match 1070, 1104
- \@affilID@temp 43–45
- \@affilID@temp .. 968, 969, 1023
- \@affilclear@sw 23
- \@affilclear@sw 402, 422
- \@affilcomma . 1005, 1008, 1014, 1016, 1030
- \@affiliation 388, 390
- \@affils@sw 16, 17, 24
- \@affils@sw . 239, 244, 250, 256, 262, 425
- \@argswap 328, 330
- \@argswap@val 333, 335, 444, 448, 451, 452, 702, 906
- \@author 20, 23, 30
- \@author . 306, 309, 318, 321, 323, 334
- \@author@cleared 20
- \@author@cleared 303, 928
- \@author@count .. 925, 948, 1107
- \@author@def 295, 298, 303
- \@author@finish 23
- \@author@finish . 344, 827, 1292
- \@author@gobble 20
- \@author@gobble .. 304, 520, 950, 966, 1109, 1118

<code>\@author@init</code>	20	<code>\@if@empty</code> ..	374, 606, 972, 977, 992, 1134, 1157, 1170, 1222
<code>\@author@init</code>	<u>303</u> , 338	<code>\@if@sw</code>	1321
<code>\@author@join</code>	<u>303</u>	<code>\@ifdim</code>	801
<code>\@author@join@</code>	<u>303</u>	<code>\@ifhmode</code>	1237
<code>\@author@parskip</code>	1038	<code>\@ifnextchar</code>	852
<code>\@author@present</code>	16, 30, 48	<code>\@ifnum</code> ..	478, 587, 596, 598–600, 984, 988, 1034, 1064, 1084, 1125, 1130
<code>\@author@present</code> .	920, 932, 958, 1041, 1116	<code>\@ifundefined</code>	29
<code>\@author@present@group</code>	32	<code>\@ifvmode</code>	1223
<code>\@author@present@group</code> ..	1041, <u>1142</u>	<code>\@ifx</code>	50
<code>\@author@present@script</code>	31	<code>\@ifx</code>	309, 347, 348, 353, 359, 413, 432, 433, 442, 476, 499, 500, 511, 512, 526, 612, 621, 808, 860, 907, 971, 1006, 1007, 1012, 1013, 1026, 1027, 1080, 1106, 1115, 1123, 1132, 1199, 1243
<code>\@author@present@script</code> ..	920, <u>998</u>	<code>\@ifx@empty</code>	889, 892
<code>\@authorclear@sw</code>	20	<code>\@ifxundefined</code> 1190–1194, 1282, 1287	
<code>\@authorclear@sw</code>	<u>303</u> , 325	<code>\@iiiparbox</code>	35
<code>\@booleanfalse</code>	235, 236, 238, 240, 245, 250, 251, 261, 263, 301, 307, 423, 518, 630, 1191, 1320, 1321	<code>\@issuenummer</code>	1252, 1253
<code>\@booleantrue</code> 234, 237, 239, 243, 244, 249, 255–257, 262, 298, 490, 613, 622, 1199, 1282, 1289, 1321		<code>\@join</code>	22
<code>\@collaboration@count</code> .	926, <u>964</u>	<code>\@join</code>	285, 321, <u>373</u> , 418
<code>\@collaboration@gobble</code>	<u>601</u> , 1111, 1120	<code>\@keys@name</code>	1167
<code>\@collaboration@present</code> ..	933, <u>952</u> , 1046	<code>\@keywords</code>	669, 892, 893
<code>\@currentlabel</code>	736	<code>\@keywords@produce</code> ..	893, <u>1163</u>
<code>\@date</code>	57	<code>\@listand</code>	30
<code>\@date</code>	<u>676</u> , 882	<code>\@listand</code>	598, 607, 1102
<code>\@eid</code>	1254, 1255	<code>\@listcomma</code>	30, 31, 42, 43
<code>\@email</code>	560, 561	<code>\@listcomma</code> .	581, 583, 588, 590, 599, 603, 1048, 1085, 1102
<code>\@empty</code>	28	<code>\@listcomma@comma</code>	583, 590, 599
<code>\@endpage</code>	1259, 1260	<code>\@listcomma@comma@UK</code>	600
<code>\@finalstrut</code>	739	<code>\@listdepth</code>	715
<code>\@firstofone</code>	377, 378, 1193	<code>\@makefnmark</code>	663, 872, 975, 989, 1209
<code>\@fnsymbol</code>	52	<code>\@makefntext</code>	36
<code>\@fnsymbol</code>	1197	<code>\@makeother</code>	556–558
<code>\@footnotemark</code>	32	<code>\@maketitle</code>	55
<code>\@footnotemark</code>	848, 850	<code>\@maketitle</code>	1287, 1291
<code>\@footnotetext</code>	712, 849, 851	<code>\@minipagefalse</code>	727
<code>\@homepage</code>	30	<code>\@minipagerestore</code>	717
<code>\@homepage</code>	565, 566	<code>\@mpfn</code>	639, 644, 661, 711,

736, 869, 1182, 1197, 1208,
1318, 1337

`\@mpfootnotetext` 36

`\@mplistdepth` 715

`\@ne` 31, 45

`\@pacs` 686, 889, 890

`\@pacs@name` 1154

`\@pacs@produce` 890, 1150

`\@parboxrestore` 710, 735

`\@preprint` 693, 695

`\@provide` 1038, 1055

`\@published` 676, 886

`\@received` 34

`\@received` 676, 883

`\@reset@ac` 580, 593

`\@revised` 676, 884

`\@secondofthree` 356, 357, 372

`\@secondoftwo` 355

`\@separator` 285, 321, 376, 418

`\@setminipage` 718

`\@shorttitle` 275, 278

`\@startpage` 54

`\@startpage` 1257, 1258

`\@starttoc` 1269

`\@tempa` 24, 25, 28, 42–44, 46

`\@tempa` 426, 427, 435, 631,
633, 971, 1022, 1027, 1030,
1034, 1131, 1132

`\@tempb` 25, 32, 33

`\@tempb` 431–433, 623, 632, 637

`\@tempc` 24, 25

`\@tempc` 443, 447, 458, 491

`\@tempcnt` 42

`\@tempcnta` 30, 31, 42, 47, 48

`\@tempd` 24, 25

`\@tempd` 424, 433, 492

`\@tempfix` 475, 476, 611, 612, 620,
621, 971, 1105, 1106, 1114,
1115

`\@textsuperscript` 1201

`\@tfor` 1079

`\@thanks` 1311

`\@thefnmark` 662, 736, 975, 989,
1183, 1202

`\@title` 274, 278, 904, 906

`\@title@aux` 281, 283, 285, 907,
908

`\@title@aux@cleared` 281, 283,
907

`\@title@join` 276, 283

`\@title@join@` 283

`\@undefined` 48

`\@undefined` 841, 1060, 1061, 1068,
1069, 1199

`\@volumenumber` 1250, 1251

`\@volumeyear` 1248, 1249

`\@x@sf` 658, 666

`\@` 54, 56

`\{` 137

`\cmd@_@october@6,@2020, argument`
. 57

`\}` 137

`_` 50, 558

`\~` 557

00readme 4

10pt document class option . . . 69

11pt document class option . . . 69

12pt document class option . . . 69

`□` 69, 72

`\□` 38, 44, 67, 68, 72, 91, 97, 103,
107, 116, 144, 216, 1102

A

`\absbox` 35

`\absbox` 697, 706, 799, 805

`\abstract` 841

abstract (environment) 698

abstract environment 2, 14, 35

`\abstractname` 702, 764

`\accepted` 34

`\accepted` 676

`\Accepted@name` 682, 1273

`\active` 380

`\active@comma` 381, 382

`\add@AUCC@grp` 21

`\add@AUCC@grp` 324

`\add@list@val@val@val` 25

`\add@list@val@val@val` 453, 469

`\addcontents@abstract` 699, 722

`\addcontentsline` 702, 906
`\langle address \rangle` placeholder 29
`\AF@grp` 25–28
`\AF@grp` . . . 353, 458, 459, 498, 499, 509, 519, 524, 534, 538
`\AF@opr` 26–28, 43, 44, 47, 49
`\AF@opr` . . 502, 508, 924, 931, 1062, 1070
`\AF@temp` 47
`\AF@temp` . . 1058, 1062, 1070, 1079, 1080
`\AFF@opr` . . . 23, 25, 28, 44, 45, 50
`\AFF@opr` 427, 453, 941, 1095
`\affil@cutoff` 31, 45
`\affil@cutoff` 988, 997
`\affil@present@script` 970
`\affil@script` 28, 44
`\affil@script` 970
`\affiliation` . . 10, 12, 13, 22, 23, 28, 29
affiliation, argument 12
`\affiliation` . . 204, 208, 380, 831
`\langle affiliation ID \rangle` placeholder . . . 29
`\affils@present@group` . . . 31, 53
`\affils@present@group` . . . 1047, 1056
`\affils@present@script` . . . 970
`\AFG@opr` 27, 28, 32, 44, 47
`\AFG@opr` 519, 523, 1047
`\after@address` 49
`\after@address` . . 1093, 1102, 1103, 1137
`\aftergroup` 31, 46, 50
`\aftergroup` . . . 1028, 1031, 1148
`\aftermaketitle@chk` . . 670, 687, 705, 1242
`\altaffiliation` 12, 13, 18, 29, 31
`\altaffiliation` 551, 576
`\altaffilletter@sw` . . 1197, 1199, 1320
`\and` 19, 22, 56
`\and` . . . 379, 830, 1297, 1298, 1325
`\and@latex` 1297
`\and@space` 1325, 1339
`\andname` 598, 1340
`\appdef` 21, 25
`\appdef` 271, 278, 290, 300, 310, 341, 404, 470, 502, 508, 523, 538, 546, 570, 653, 673, 690, 694, 811, 859, 914, 1034, 1093, 1189, 1278
`\appdef@e` 503, 504, 510, 527, 528
`\appdef@eval` 458, 509, 524, 965
`\appendix` 1268
`\appendix@toc` 54
`\appendix@toc` 1268, 1272
argument
 `\cmd_0ctober_6_2020` 57
 affiliation 12
 e-mail_address 12
 miscellaneous_text 12
 title 10
 URL 12
argument, optional
 optional_text 12
article document class 19, 38, 55
`\AU@grp` 20, 21, 26–28
`\AU@grp` . . . 330, 347, 361, 498, 510, 511, 533, 538
`\AU@opr` 21, 28, 43, 45, 47, 50
`\AU@opr` 330, 356, 925, 932, 1060, 1068, 1107, 1109, 1116, 1118
`\AU@temp` 42
`\AU@temp` 922, 926, 933, 934, 1044–1046
`auguide.tex` 3
`\author` . . . 10–13, 19, 22, 27–29, 31, 56
`\langle author \rangle` placeholder 29
`\author` . . . 48, 202, 206, 294, 314, 832, 1285
`\langle auxiliary info \rangle` placeholder . . . 29
`\langle auxilliary info \rangle` placeholder . . . 29

B

`\baselineskip` 798, 814, 815, 917, 1325
bibnotes document class option 14
`\blankaffiliation` 50
`\blankaffiliation` 401, 1132
`\break` 1237

C

`\c@affil` 19
`\c@affil` [288](#), 446–448, 988
`\c@collab` 19
`\c@collab` [288](#), 327, 335, 451, 478
`\c@mpfootnote` 711, 871
`\c@page` 1257
`\cat@comma@active` 380, 381, 387
`\catcode` 380
`\centering` 763, 1323, 1325, 1329, 1330
`\changes` 141–192
`\class@documenthook` 18
`\class@documenthook` . 271, 570, 859
`\class@err` 379, 1244
`\class@info` 861
`\class@name` 230
`\class@warn` 55
`\class@warn` . 279, 360, 363, 434, 550, 756, 1158, 1171, 1279
<class customization commands> placeholder holder 10
`\classname` . 59, 66, 125, 127, 129
`\classoption` 188
`\clearpage` 844
`\clo@groupedaddress` .. 241, 242
`\clo@runinaddress` 253, 254
`\clo@superscriptaddress` .. 259, 260
`\clo@unsortedaddress` . 247, 248
`\cmd` 137
`\CO@grp` [20](#), [26–28](#), 31
`\CO@grp` .. 328, 348, 359, 364, 498, 500, 503–505, 512, 526–529, 532, 540
`\CO@opr` [27](#), [28](#), 48
`\CO@opr` 328, 357, 520, 926, 928, 933, 1046, 1061, 1069, 1111, 1120
`\collaboration` [10](#), [12](#), [13](#), [19](#), [20](#), [24](#), [26–29](#)
`\collaboration` [297](#), 314
`\collaboration@sw` 298, 301, 307, 326, [1189](#)
<collaboration ID> placeholder . 29

`\color@begingroup` 707, 737
`\color@endgroup` 728, 741
`\columnwidth` 708, 709
`\comma@space` .. 606, 1000, 1143, [1189](#)
`\copyright` 44
`\count` 43
`\count@` 50
`\count@` 1124, 1125, 1130
`\cs` . 141, 144, 146, 147, 149, 153, 161, 162, 165, 166, 168–170, 172, 173, 176–181, 184–190
`\csname` [29](#), [33](#), [39](#), 43
`\csname` 30, 644, 661, 701, 736, 1182, 1197, 1208, 1266, 1318, 1337

D

`\date` [10](#), [34](#), [55–57](#)
<date> placeholder 10
`\date` 210, [676](#), 1286
`\Dated@name` 676, [1273](#)
`\def@after@address` . 1087, [1102](#)
`\def@after@address@empty` [1102](#)
`\dimen@` 798, 800, 801
`\do` 1079
`\do@affil@fromgroup` 50
`\do@affil@fromgroup` 1096, [1122](#)
`\do@output@MVL` 788, [1189](#)
`\do@title` 273
`\doauthor` [31](#), [32](#), [44](#), [46](#), 50
`\doauthor` [602](#), 1001, 1144
`doc` 4
`\DocInput` 9
`docstrip document class` 16
document class
 `article` [19](#), [38](#), 55
 `docstrip` 16
 `frontmatter` 18
 `hyperref` [32](#), [35](#), [36](#), [39](#), [52](#), 74
 `lineno` 73, 75
 `ltxdoc` 4, 9
 `ltxfront` 2, 15, 56
 `ltxgrid` 55, 75
 `ltxutil` 16, 36, 52
 `multicol` 69

\frontmatter@abstractfont 35,
36
\frontmatter@abstractfont 720,
768
\frontmatter@abstractheading
..... 35
\frontmatter@abstractheading
..... 719, 761
\frontmatter@abstractwidth 35
\frontmatter@abstractwidth 784
\frontmatter@addressnewline .
..... 1077, 1236
\frontmatter@affiliationfont
..... 45
\frontmatter@affiliationfont
. 987, 1076, 1231, 1329
\frontmatter@and 55
\frontmatter@and 379, 1298
\frontmatter@author 55
\frontmatter@author . 294, 1285
\frontmatter@author@produce 41,
47
\frontmatter@author@produce@group
..... 47
\frontmatter@author@produce@group
..... 877, 1039
\frontmatter@author@produce@script
..... 41, 43
\frontmatter@author@produce@script
..... 879, 918
\frontmatter@authorbelow 1053,
1055, 1326
\frontmatter@authorformat 930,
1042, 1227, 1325
\frontmatter@collaboration@above
..... 955, 963
\frontmatter@date 55
\frontmatter@date ... 676, 1286
\frontmatter@description . 769
\frontmatter@descriptionlabel
..... 774, 779
\frontmatter@finalspace .. 896,
1235
\frontmatter@foot@mark 33
\frontmatter@foot@mark 641, 649
\frontmatter@footnote 606, 628,
908, 977, 992, 1135
\frontmatter@footnote@produce
.... 943, 1050, 1189
\frontmatter@footnote@produce@endnote
..... 1175
\frontmatter@footnote@produce@footnote
..... 1175, 1192
\frontmatter@footnotemark 636,
650, 656
\frontmatter@footnotetext 712,
731, 1184, 1332
\frontmatter@init 18
\frontmatter@init 271, 278, 290,
300, 310, 404, 538, 546, 653,
673, 690, 694, 811, 1189
\frontmatter@keys@format 1166,
1234
\frontmatter@makefnmark .. 872,
1200
\frontmatter@makefntext ... 36
\frontmatter@makefntext .. 738,
1205
\frontmatter@maketitle 55
\frontmatter@maketitle ... 826,
862, 1288, 1291
\frontmatter@noaffiliation 395,
1294
\frontmatter@PACS@format 1153,
1233
\frontmatter@postabstractspace
.... 809, 814, 1240
\frontmatter@preabstractspace
789, 795, 814, 1240, 1331
\frontmatter@RRAP@format .. 52
\frontmatter@RRAP@format 1216,
1232, 1330
\frontmatter@RRAPformat ... 52
\frontmatter@RRAPformat .. 881,
1213
\frontmatter@setup .. 873, 1212
\frontmatter@syntax@sw ... 236,
237, 1282, 1283
\frontmatter@thanks 55
\frontmatter@thanks . 573, 1296
\frontmatter@thefootnote . 662,
1183, 1196

<code>\frontmatter@title</code>	55	<code>\Hy@saved@footnotemark</code>	...	848
<code>\frontmatter@title</code>	..	273, 1284	<code>\Hy@saved@footnotetext</code>	...	849
<code>\frontmatter@title@above</code>	..	41	<code>\HyOrg@maketitle</code>	855
<code>\frontmatter@title@above</code>	..	902, 915, 1322	<code>\hyper@anchorend</code>	1208
<code>\frontmatter@title@below</code>	..	41	<code>\hyper@anchorstart</code>	1208
<code>\frontmatter@title@below</code>	..	911, 915, 1324	<code>\hyper@linkend</code>	664
<code>\frontmatter@title@format</code>	..	41	<code>\hyper@linkstart</code>	660
<code>\frontmatter@title@format</code>	..	903, 915, 1323	hyperref document class	..	32, 35, 36, 39, 52, 74
<code>\frontmatter@title@produce</code>	..	875, 899	hypertext document class option	..	73
<code>frontmatter@titlepage</code> environment	55	I		
<code>\frontmatterverbose@sw</code>	16	<code>\if@titlepage</code>	55
<code>\frontmatterverbose@sw</code>	...	234, 235, 314, 342, 345, 361, 364, 384, 396, 459, 471, 498, 536, 921, 1043	<code>\if@titlepage</code>	1321
G			<code>\iffalse</code>	52
<code>\g@addto@macro</code>	651	<code>\ifx</code>	47
<code>\gappdef</code>	693, 1309	<code>\ignorespaces</code>	..	603, 739, 958, 975, 991, 1223
<code>\GetFileInfo</code>	35	<code>\issuenummer</code>	1252
groupauthors document class option	69	<code>\item</code>	..	101, 106, 117, 120, 124, 126, 128, 133, 135
<code>\groupauthors@sw</code>	..	16, 17, 25, 47	<code>\itemindent</code>	773
<code>\groupauthors@sw</code>	..	240, 243, 249, 255, 261, 477, 876	<code>\itshape</code>	1231, 1329
<code>\groupedaddress</code>	241	K		
groupedaddress document class option	..	11, 17, 28, 31, 47, 49, 50, 53	<code>\keywords</code>	14, 34
H			<code>\keywords</code>	669
<code>\H@@footnotemark</code>	850	L		
<code>\H@@footnotetext</code>	851	<code>\l@section</code>	54
<code>\homepage</code>	..	10, 12, 13, 18, 29–31	<code>\label</code>	874
<code>\homepage</code>	551, 565	<code>\labelsep</code>	780
<code>\href</code>	355, 563, 568, 570	<code>\labelwidth</code>	772
<code>\ht</code>	800	<code>\LARGE</code>	1323
<code>\Hy@maketitle@end</code>	856	<code>\large</code>	763, 1325, 1330
<code>\Hy@maketitle@optarg</code>	853	<code>\lastskip</code>	1237
<code>\Hy@raisedlink</code>	52	<code>\LaTeX</code>	..	38, 67, 68, 78, 88, 91, 107, 113, 116, 118, 144, 216
<code>\Hy@raisedlink</code>	1208	<code>\LaTeXe</code>	72, 97, 227
			<code>\leftmargin</code>	771
			<code>\let@environment</code>	..	716, 1299, 1300
			<code>\let@mark</code>	914
			lineno document class	..	73, 75
			<code>\listand</code>	42
			<code>\listand</code>	598
			<code>\listcomma</code>	42

<code>\ltx@footnote@pop</code>	868	<code>\move@AUAF</code>	315, 370, 399, 497		
<code>\ltx@no@footnote</code>	744	<code>\mp@footnotetext</code>	36		
<code>\ltx@no@footwarn</code>	744	multicol document class	69		
<code>\ltx@no@xfootmark</code>	746, 751	N			
<code>\ltx@no@xfootnote</code>	745, 749	<code>\newbox</code>	697		
<code>\ltx@no@xfoottext</code>	747, 753	<code>\newcounter</code>	19		
<code>\ltx@no@yfootmark</code>	746, 752	<code>\noaffiliation</code>	12 , 21 , 23 , 24 , 26 , 45 , 46 , 49 , 50		
<code>\ltx@no@yfootnote</code>	745, 750	<code>\noaffiliation</code>	360, 363, 395 , 1294, 1302		
<code>\ltx@no@yfoottext</code>	747, 754	nobibnotes document class option	14		
<code>\ltx@xfootmark</code>	746	<code>\normalfont</code>	781, 1202		
<code>\ltx@xfootnote</code>	745	noshowkeys document class option	15		
<code>\ltx@xfoottext</code>	747	noshowpacs document class option	14		
<code>\ltx@yfootmark</code>	746	O			
<code>\ltx@yfootnote</code>	745	<code>\onecolumngrid</code>	817		
<code>\ltx@yfoottext</code>	747	optional _␣ text, optional argument	12		
ltxdoc document class	4, 9	<code>\OptionNotUsed</code>	267		
ltxfront	2 , 56	P			
ltxfront document class	2 , 15 , 56	package	2 , 15		
ltxgrid document class	55 , 75	<code>\package@name</code>	225, 226, 230		
ltxutil document class	16 , 36 , 52	<code>\PackageInfo</code>	226		
M				<code>\pacs</code>	14
<code>\makeatletter</code>	28	<code>\pacs</code>	686		
<code>\makeatother</code>	31	<code>\PACS@warn</code>	1158, 1162		
<code>\makelabel</code>	774	<code>\pageref</code>	1258, 1260		
<code>\maketitle</code>	10 , 14 , 15 , 18 , 34 , 35 , 39 , 54–57	<code>\parindent</code>	35		
<code>\maketitle</code>	57, 213, 826 , 860–862, 1243, 1244, 1288, 1292	<code>\parindent</code>	1206		
<code>\maketitle@Hy</code>	847	<code>\parskip</code>	35		
<code>\mini@note</code>	36	<code>\parskip</code>	1091, 1325		
<code>\mini@note</code>	721	<code>\phantomsection</code>	700, 906		
<code>\mini@notes</code>	808, 811	placeholder			
<code>\minipage</code>	35	<code><address></code>	29		
minipage environment	35	<code><affiliation ID></code>	29		
<code>\minipagefootnote@drop</code>	742	<code><author></code>	29		
<code>\minipagefootnote@here</code>	726	<code><auxiliary info></code>	29		
<code>\minipagefootnote@init</code>	713	<code><auxiliary info></code>	29		
<code>\minipagefootnote@pick</code>	732	<code><class customization commands></code>	10		
miscellaneous _␣ text, argument	12				
<code>\move@AF</code>	19 , 25				
<code>\move@AF</code>	315, 346, 367, 385, 397, 398 , 421				
<code>\move@AU</code>	19–21				
<code>\move@AU</code>	315, 324 , 346, 385, 397				
<code>\move@AUAF</code>	19				

<collaboration ID> 29
<date> 10
<your document here> 9
\post@absbox 806, 813
\prep@absbox 804, 812
\prepdef 1292
\preprint 15
\preprint 693
preprint document class option 14
\preprintsty@sw 787, 1189
\present@bibnote 51
\present@FM@footnote 1176, 1180
\prevdepth 800
\print@toc 1261
\produce@RRAP 52
\produce@RRAP ... 882–886, 1213
\protected@edef 736
\providecommand 571
\ProvidesFile 6
\ps@empty 1247
\ps@titlepage 1247
\published 34
\published 676
\Published@name 684, 1273
\punct@RRAP 52
\punct@RRAP 1213

R

README 3
\received 34
\received 676
\Received@name 678, 1273
\RecordChanges 33
\relax 23, 39, 46, 49
\removelastskip 1214
\RequirePackage . 25, 27, 30, 231
\revised 34
\revised 211, 676
\Revised@name 680, 1273
revtex4 document class 53
revtex4-1 document class 1
\robustify@contents 1278
\rule 739
\runinaddress 253
runinaddress document class op-
tion 16, 17,

47

\runinaddress@sw 16, 17
\runinaddress@sw . 238, 245, 251,
257, 263, 1088

S

\sanitize@url 555, 560, 565
\say 342, 361, 364, 459, 471, 498,
536, 921, 1043
\sc 88
\section 54
\section 84, 215, 1263
\set@footnotefont 733
\set@footnotewidth 734
\set@listcomma@count 30
\set@listcomma@count 579, 1067
\set@listcomma@list 30
\set@listcomma@list . 579, 934,
961, 1045
\set@listindent 714
\set@listindent@ 714
showkeys document class option 15
\showKEYS@sw 1164
showpacs document class option 14
\showPACS@sw 1151
\skip@ 1237
\spacefactor 658, 666
\special 35
\startpage 1257
\stepcounter 639
\StopEventually 5
\string .. 314, 345, 360, 363, 384,
396, 551, 757, 758, 861, 921,
1043, 1280
\strutbox 739
\subsection 94, 140
\superscriptaddress 259
superscriptaddress document class
option 11, 12, 17, 22, 25,
31, 41, 43–45, 53, 74
\suppressfloats 829
\surname 14
\surname 377

T

\tableofcontents 82

<code>\temp@sw</code>	24, 25, 33	<code>\unpenalty</code>	1237
<code>\temp@sw</code> .	423, 429, 474, 490, 518, 522, 610, 613, 619, 622, 630, 635	<code>\unskip</code> ..	603, 725, 905, 936, 958, 1223, 1237
<code>template.aps</code>	3	<code>\unsortedaddress</code>	247
<code>\TeX</code>	72, 103, 118	<code>unsortedaddress</code> document class option	11, 12, 16, 17, 47
<code>\textsuperscript</code>	46	<code>\unvbox</code>	805
<code>\textsuperscript</code> ..	1000, 1030, 1143	<code>\unvcopy</code>	799
<code>\texttt</code> ..	50, 114, 115, 122, 131, 134, 137, 164, 165, 184	URL, argument	12
<code>\textwidth</code>	708, 784	<code>\url</code>	26, 63, 69
<code>\thanks</code> .	10, 12, 13, 18, 29–31, 56		
<code>\thanks</code>	39, 43, 50, 203, 207, 551, 573, 758, 840, 1279, 1295, 1296, 1323, 1325	V	
<code>\thanks@latex</code> .	1295, 1306, 1323, 1325	<code>\vadjust</code>	739
<code>\the</code>	19, 33	<code>\vbox</code>	706
<code>\theaffil</code>	19	<code>\volumenumber</code>	1250
<code>thebibliography</code> environment	75	<code>\volumeyear</code>	1248
<code>\thecollab</code>	19	<code>\vtop</code>	799
<code>\thempfn</code>	711, 870		
<code>\thempfootnote</code>	711, 870	X	
<code>\thispagestyle</code>	818, 874	<code>\x@match</code>	32
<code>\tightenlines@sw</code>	1090	<code>\x@match</code>	519, 609
<code>\title</code>	10, 13, 18, 55, 56	Y	
<code>title</code> , argument	10	<code>\y@match</code>	32
<code>\title</code>	37, 200, 273, 1284	<code>\y@match</code>	618, 633
<code>\title@column</code>	828, 1189	<code>\your document here</code> placeholder	9
<code>\titleblock@produce</code> ..	828, 866		
<code>titlepage</code> (environment) ...	816	Z	
<code>\titlepage@sw</code> ..	842, 1289, 1321	<code>\z@</code>	49
<code>\toclevel@abstract</code>	698	<code>\z@skip</code>	739, 1038
<code>\toclevel@title</code>	899		
<code>\today</code>	10, 57		
<code>\true@sw</code>	31, 32		
<code>\true@sw</code>	479, 484, 1031		
<code>\tw@</code>	31, 45		
<code>\twocolumn@sw</code>	817, 821		
<code>\twocolumngrid</code>	821		
<code>\twoside@sw</code>	822		
U			
<code>\undefined</code>	39		

Change History

4.0a	Defer assignment until	
General: 4.0d had twoside option	<code>\AtBeginDocument</code> time.	3
setting twoside switch to false . . .	Defer decision until	
comma not space between email	<code>\AtBeginDocument</code> time	3
and homepage	Define three separate	
Initial version	environments, defer assignment	
Move after process options, so	to <code>\AtBeginDocument</code> time.	3
<code>\clearpage</code> not in scope of	First modifications by Arthur	
<code>twocolumn</code>	Ogawa (mailto:arthur_ogawa at	
Move after process options, so	sbcglobal dot net)	3
the following test works	Frank Mittelbach, has stated in	
multiple preprint commands	<code>multicol</code> : “The kernel	
print homepage	command <code>\@footnotetext</code>	
protect against hyperref revtex	should not be modified.” Thus,	
kludges which are not needed	I have removed David	
now	Carlisle’s redefinition of that	
Rearrange the ordering so	command. Note, however, that	
numerical ones come first. AO:	later versions of <code>multicol</code> do	
David, what does this mean? . . .	not require this workaround.	
single space footnotes	Belt and suspenders.	3
use font-dependent spacing	Gathered all code for the	
4.0b	abstract environment together	
<code>\@author@join</code> : Change handling	and abstracted out the	
of <code>\@author</code> to prevent parsing	formatting details for journals	
problems. (Helps in error	to override.	35
recovery when syntax errors	Move this “complex” option to	
exist)	the front, where it can be	
<code>\@pacs@produce</code> : Separate option	overridden by “simple” options.	3
now controls production	New option	3
<code>\titleblock@produce</code> : Set	One-line caption sets flush left.	3
<code>\footnote</code> to L ^A T _E X standard	only execute if appropriate	3
version for this scope.	Processing delayed to	
General: Added localization of	<code>\AtBeginDocument</code> time	3
<code>\figuresname</code>	Removed invocation of	
Added localization of	nonexistent class option	
<code>\tablename</code>	<code>groupauthors</code> and all other	
AO: all code for 10pt is in this	class options that should only	
module.	be invoked by the document.	
AO: all code for 11pt is in this	(Otherwise precedence of class	
module.	options does not work.)	3
AO: all code for 12pt is in this	Restore all media size class	
module.	option of <code>_classes.dtx</code>	3
AO: made aps.rtx part of	Stack <code>\preprint</code> args flush right	
<code>revtex4.dtx</code>	at right margin.	3
AO: remove duplicates	4.0c	
call <code>\print@floats</code>	General: (AO, 115) If three or	
	more preprints specified, set on	

single line, with commas.	3	<code>\@pacs@produce</code> : Warn if no	
(AO, 129) section* within		production	50
appendix was producing		General: adornments above and	
appendixname	3	below.	3
*-form mandates pagebreak . . .	3	Bug fixes and minor new	
also spelled		features: title block affiliations	
“acknowledgements”.	3	can have ancillary data, just	
Do not put by REVTeX in every		like authors; clearpage	
page foot	3	processing revamped, with	
grid changes via ltxgrid		floats staying in order;	
procedures	3	widetext ornaments.	3
grid changes with ltxgrid	3	New option showkeys	3
Insert procedure <code>\checkindate</code> .	3	4.0f	
Lose compatibility mode.	3	<code>\@author@finish</code> : Actually	
New ltxgrid-based code, other		append <code>\AU@grp</code> to <code>\@ACLlist</code>	21
bug fixes	3	General: Last bug fixes before	
New option “checkin”	3	release.	3
Prevent an inner footnote from		4.0g	
performing twice	3	General: multiple preprint	
<code>titlepage</code> : grid changes with		commands	35
ltxgrid	38	4.0h	
4.0d		<code>\@author@present@script</code> :	
<code>\@affil@present@group</code> :		Changes to support groups of	
<code>\comma@space</code>	50	affiliations	45
<code>\@pacs@produce</code> : PACS boxed to		<code>\frontmatter@addressnewline</code> :	
width of abstract	50	new hook	54
<code>\altaffiliation</code> : change name		<code>\move@AUAF</code> : Changes to support	
from <code>\tempaffiliation</code>	30	groups of affiliations	26
<code>\maketitle</code> : hookify	39	4.0l	
General: Also alter how lists get		<code>\altaffiliation</code> : add optional	
indented.	3	argument handling back	30
But alternative spelling is		<code>\frontmatter@author@produce@script</code> :	
deprecated.	3	Changes to add collaboration	
eprint takes an optional		processing, which now means	
argument, syntactical only in		doing comma/and processing	
this case.	3	on each sublist	42
make longtable trigger the head,		<code>\set@listcomma@count</code> : macro	
too	3	added	30
More features and bug fixes:		4.0rc1	
compatibility with longtable		General: grid changes with push	
and array packages. Now		and pop	3
certainly incompatible with		Running headers always as if	
multicol.	3	two-sided	3
New option	3	4.0rc4	
<code>abstract</code> : hookify	35	General: hyperref is no longer	
If empty <code>\abstractname</code> omit		loaded via class option: use a	
spacing	35	usepackage statement instead	3
4.0e		4.1a	
<code>\@keywords@produce</code> : Keywords		<code>\@affil@present@script</code> : removed	
on same footing as PACS	51	code that had been commented	

out	44	groupedaddress	20
\affils@present@script:		Use \frontmatter@init as the	
removed code that had been		vehicle for all initialization ..	20
commented out	44	\@published: Make the syntax of	
\email: (AO, 496) remove default		this package switch optional ..	34
prependation to \email.	29	\@shorttitle: Use	
\homepage: (AO, 496) remove		\frontmatter@init as the	
default prependation to		vehicle for all initialization ..	18
\homepage.	30	\add@AUCC@grp: (AO, 486)	
General: (AO, 451) “Cannot have		\collaboration to work with	
more than 256 cites in a		groupedaddress	20
document”	3	Provide for diagnostics via	
(AO, 457) Endnotes to be sorted		\frontmatterverbose@sw ...	21
in with numerical citations. ...	3	\affiliation: Use \@affil@def	
(AO, 460) “Proper style is		for all access to \@affil	22
”FIG. 1. ...” (no colon)”	3	\affils@present@group: Provide	
(AO, 461) Change the cfname		for diagnostics via	
revtex uses from @dotsep to		\frontmatterverbose@sw ...	47
ltxu@dotsep. The former is		\author: Make the syntax of this	
understood in mu. (What we		package switch optional	19
wanted was a dimension.)	3	\c@collab: (AO, 486)	
(AO, 478) \ds@letterpaper, so		\collaboration to work with	
that “letterpaper really is the		groupedaddress	19
default”	3	\collaboration: (AO, 486)	
(AO, 488) Change processing of		\collaboration to work with	
options to allow an unused		groupedaddress	19
option to specify society and		\do@title: Make the syntax of	
journal	3	this package switch optional ..	18
For natbib versions before 8.21,		\doauthor: Provide facility	
\NAT@sort was consulted only		\affil@cutoff: if there is only	
as natbib was being read in.		one affiliation on the title page,	
Now it is fully dynamic.	3	no superscript	31
abstract: (AO, 443) create an		\frontmatter@author@produce@group:	
entry in the PDF bookmarks		Provide for diagnostics via	
for the abstract via the toc ..	35	\frontmatterverbose@sw ...	47
4.1b		\frontmatter@author@produce@script:	
\@affil@join: Use \@affil@def		Provide for diagnostics via	
for all access to \@affil	23	\frontmatterverbose@sw ...	41
\@affil@match: (AO, 486)		\frontmatter@title@produce:	
\collaboration to work with		(AO, 443) PDF Bookmark for	
groupedaddress	25	title page	41
\@author@finish: (AO, 486)		\move@AF: (AO, 486)	
\collaboration to work with		\collaboration to work with	
groupedaddress	21	groupedaddress	24
Provide for diagnostics via		Provide for diagnostics via	
\frontmatterverbose@sw ...	21	\frontmatterverbose@sw ...	25
Use \@affil@def for all access		\move@AUAF: (AO, 486)	
to \@affil	21	\collaboration to work with	
\@author@join: (AO, 486)		groupedaddress	26
\collaboration to work with			

Change cname <code>\AFS@opr</code> to <code>\AFG@opr</code>	26	Make the syntax of this package switch optional	55
Provide for diagnostics via <code>\frontmatterverbose@sw</code> . . .	26	Package <code>textcase</code> is now simply a required package	3
<code>\noaffiliation</code> : Use <code>\@affil@def</code> for all access to <code>\@affil</code>	23	Procedures <code>\@parse@class@options@society</code> and <code>\@parse@class@options@journal</code> and friends	3
<code>\thanks</code> : Make the syntax of this package switch optional	30	Rag the right even more: <code>.8\hsize</code> . Also, assign <code>\@totalleftmargin</code>	3
General: (AO) Implement bibnotes through <code>\frontmatter@footnote@produce</code> instead of <code>\bibnotes@sw</code>	3	Read in all required packages together	3
(AO) No longer need to test <code>\chapter</code> as of <code>natbib</code> version 8.2	3	Remove options <code>newabstract</code> and <code>oldabstract</code>	3
(AO) No longer use <code>\secnumarabic@sw</code> , instead use <code>\setup@secnums</code>	3	Section numbering via procedures <code>\secnums@rtx</code> and <code>\secnums@arabic</code>	3
(AO) Provide more diagnostics when <code>\@society</code> is assigned. . . .	3	The <code>rmp</code> journal substyle selects <code>groupedaddress</code> by default. . . .	3
(AO) Structure the Abstract using the <code>bibliography</code> environment	3	The <code>cname</code> substyle@ext is now defined without a dot (<code>.</code>), to be compatible with <code>L^AT_EX</code> usage (see <code>@clsexextension</code> and <code>@pkgextension</code>).	3
(AO) coordinate <code>\if@twoside</code> with <code>\twoside@sw</code>	3	Use <code>\setup@hook</code> to initialize all. <code>frontmatter@description</code> : (AO, 455) provide a <code>description</code> environment for the abstract . .	37
(AO) make settings at class time instead of deferring them to later.	3	<code>titlepage</code> : Make the syntax of this package switch optional . .	38
(AO) provide option <code>longbibliography</code>	3	<code>\def@after@address@empty</code> : Parametrize the production after the address	49
(AO, 455) Be nice to a list within the abstract (assign <code>\@totalleftmargin</code>).	3	<code>\maketitle@Hy</code> : Hyperref compatibility: take <code>\maketitle</code> back.	39
Add <code>\@hangfroms@section</code>	3	<code>\titleblock@produce</code> : Produce PACS, keywords only if specified	40
Add option reprint, opposite of preprint, and preferred alternative to <code>twocolumn</code>	3	General: Document class option <code>longbibliography</code> via <code>\substyle@post</code>	3
As with author formatting, rag the right more, and assign <code>\@totalleftmargin</code> . Also neutralize <code>\def@after@address</code>	3	<code>\@affil@group</code> : (AO, 410) compare <code>\@tempa</code> to <code>\blankaffiliation</code>	50
Break out <code>\@caption@fignum@sep</code>	3		
Class option galley sets <code>\preprintsty@sw</code> to false	3		
Code relating to new syntax for frontmatter has been placed in <code>ltxfront.dtx</code>	3		

General: Definition of <code>\@fnsymbol</code>	4.1i	<code>\@author@finish:</code> (AO, 540) More runtime diagnostics via
follows <code>fixltx2e.sty</code>	3	<code>\frontmatterverbose@sw</code> . . .
4.1e		<code>\@author@join:</code> (AO, 540) More runtime diagnostics via
General: (AO, 455) be nice to a list within the abstract	3	<code>\frontmatterverbose@sw</code> . . .
4.1f		<code>\affiliation:</code> (AO, 540) More runtime diagnostics via
<code>\frontmatter@footnotetext:</code>		<code>\frontmatterverbose@sw</code> . . .
(AO, 515) Use <code>\set@footnotefont</code> , which is defined in <code>ltxutil</code>	36	<code>\frontmatter@author@produce@group:</code> (AO, 540) More runtime diagnostics via
General: (AO, 513) Add class option <code>linenumbers: number</code> the lines a la <code>lineno</code>	3	<code>\frontmatterverbose@sw</code> . . .
(AO, 516) Merged references are separated with a semicolon . . .	3	<code>\frontmatter@author@produce@script:</code> (AO, 540) More runtime diagnostics via
(AO, 520) Automatically produce <code>\bibliography</code> command when needed	3	<code>\frontmatterverbose@sw</code> . . .
(AO, 521) Lonely bibliography head	3	<code>\move@AF:</code> (AO, 540) Rationalize code that appends to
(AO, 522) Warn if software is expired	3	<code>\AF@grp</code>
(AO, 523) Add class option <code>nomerge</code> , to turn off new <code>natbib</code> 8.3 syntax	3	<code>\move@AUAF:</code> (AO, 540) More runtime diagnostics via
(AO, 524) Makes no sense if citations are superscript numbers and so are footnotes . .	3	<code>\frontmatterverbose@sw</code> . . .
(AO, 530) <code>\@fnsymbol:</code> Failed to import <code>fixltx2e.sty</code> technology. Return to LaTeX core.	3	<code>\noaffiliation:</code> (AO, 540) More runtime diagnostics via
4.1g		<code>\frontmatterverbose@sw</code> . . .
<code>\@author@finish:</code> (AO, 535) Robustify <code>\footnote</code> while <code>\class@warn</code> is expanding its argument	21	General: (AO, 541) Defer assignment of <code>\cite</code> until after <code>natbib</code> loads
General: (AO, 525) Remove phantom paragraph above display math that is given in vertical mode	3	4.1j
(AO, 538) <code>\MakeTextUppercase</code> inappropriately expands the double backslash	3	General: (AO, 545) hypertext capabilities off by default; enable with <code>hypertext</code>
(AO, 539) Robustify <code>\class@warn</code> against TOC processing	55	(AO, 549) Repairing <code>natbib</code> 's <code>\BibitemShut</code> and <code>\bibAnnotate</code>
4.1h		(AO, 552) Repair spacing in <code>\onlinecite</code>
General: (AO) Remove expiry code in the release software	3	4.1k
		General: (AO, 554) give the <code>\newlabel</code> command syntax appropriate to the <code>hyperref</code> package
		4.1m
		<code>\@author@finish:</code> (AO, 563) <code>\collaboration</code> to work with both <code>groupedaddress</code> and <code>superscriptaddress</code>
		<code>\@collaboration@gobble:</code> (AO, 563) Let

\@collaboration@gobble parse all three arguments of \CD@opr	31	\frontmatter@makefntext: (AO, 572) Independent footnote counter for title block. Abstract footnote counter shared with body.	52
\frontmatter@author@produce@group: (AO, 563) More complete runtime diagnostics via \frontmatterverbose@sw . . .	47	\frontmatter@thefootnote: (AO, 572) Independent footnote counter for title block. Abstract footnote counter shared with body.	52
\frontmatter@author@produce@script: (AO, 563) More complete runtime diagnostics via \frontmatterverbose@sw . . .	42	\homepage: (AO) remove http:// from \href call	30
\move@AUAF: (AO, 563) \collaboration to work with both groupedaddress and superscriptaddress	27	\move@AF: (AO, 567) Handle \noaffiliation case	24
4.1n \@affil@join: (AO, 567) Handle \noaffiliation case	23	\noaffiliation: (AO, 567) Handle \noaffiliation case	23
\@affil@present@script@: (AO, 567) Handle punctuation for superscriptaddress style authors' extra information, such as \email	46	\titleblock@produce: (AO, 572) Independent footnote counter for title block. Abstract footnote counter shared with body.	40
\@author@finish: (AO, 567) Handle \noaffiliation case	21	General: (AO) fine-tune spacing above and below widetext	3
\@author@present@script: (AO, 567) Handle \noaffiliation case	45	(AO, 565) restore 4.0 behavior: invoking class option preprint implies class option preprintnumbers	3
\doauthor: (AO, 567) Handle punctuation for superscriptaddress style authors' extra information, such as \email	31	(AO, 566) restore 4.0 behavior: flush column bottoms	3
\frontmatter@footnote: (AO, 572) Independent footnote counter for title block. Abstract footnote counter shared with body.	33	(AO, 569) Use of hyperref interferes with column balancing of last page	3
\frontmatter@footnote@produce@endnote: (AO, 572) Independent footnote counter for title block. Abstract footnote counter shared with body.	51	(AO, 569) execute the after-last-shipout procedures from within the safety of the output routine	3
\frontmatter@footnotetext: (AO, 571) allow split after last line of footnote	36	(AO, 571) Interface \set@footnotewidth for determining the set width of footnotes	3
(AO, 572) Independent footnote counter for title block. Abstract footnote counter shared with body.	36	(AO, 571) class file must set \splittopskip; fine tune \skip\footins; \footnoterule defined in terms of \skip\footins	3
		(AO, 572) Independent footnote counter for title block. Abstract footnote counter shared with body.	3, 56, 57

(AO, 572) <code>\@makefn</code> and <code>\frontmatter@makefn</code> must be defined harmoniously . . .	3	production of eprint field in bibliography.	3
(AO, 573) arrange to load <code>lineno</code> after any other packages.	3	(AO, 581) Handle case: merged references, with first ending in a stop character.	3
(AO, 575) the default for journal <code>prstper</code> is <code>longbibliography</code> . . .	3	4.1p	
(AO, 576) In <code>.bst</code> files, remove support for the <code>annotate</code> field . . .	3	General: (AO, 583) Provide interface to <code>ltxgrid</code> <code>\onecolumn@grid@setup</code> and <code>\twocolumn@grid@setup</code>	3
4.1o		(AO, 584) Per MD, remove trailing space character from each journal abbreviation: it had caused an extraneous space in the <code>.bbbl</code>	3
General: (AO, 549) Remove patch to <code>natbib</code> , which is now at version 8.31a	3	4.1q	
(AO, 575) Automatically incorporate the (BibTeX-generated) <code>.bbbl</code> into an explicit <code>thebibliography</code> . . .	3	General: (AO, 586) When <code>.bbbl</code> is pasted into the document, prevent automatic bibliography inclusion.	3
(AO, 578) accommodate the possible space character preceding <code>\BibitemShut</code>	3	(AO, 588) Only write REVTeX-specific BibTeX <code>.bib</code> data if the <code>.bst</code> style is set by REVTeX.	3
(AO, 579) Endnote shall comprise their own BibTeX entry type: <code>@FOOTNOTE</code>	3	4.1r	
(AO, 580) Control <code>.bst</code> at run time.	3	General: (AO, 595) Provide <code>\lovname</code> along with other List of Videos definitions.	3
(AO, 580) Provide a document class option to turn off			